

WAAS
CH **93643**
W29A

APP CRS
296°

Rwy Idg
TDZE
Apt Elev

7250
480
501

RNAV (GPS) RWY 29

LOUISVILLE MUHAMMAD ALI INTL (SDF)

▽

▲

Circling Rwy 11 NA at night. Rwy 29 helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LPV all Cats visibility and LNAV Cats A/B visibility to RVR 5000.

MALS R

MISSED APPROACH: Climb to 3000 direct ZUSAB and on track 269° to DAMEN and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
--------------------------	--	--	-------------------------------	--------------------------------	-------

MISSED APCH FIX

Procedure NA for arrivals at FINCH on V512 eastbound.

Procedure NA for arrivals at MIXKO on V51 southbound.

MSA RW29 2.5 NM

ELEV 501	D	TDZE 480
----------	----------	----------

LOUISVILLE, KENTUCKY

Orig-D 15AUG19

LOUISVILLE MUHAMMAD ALI INTL (SDF)

38°10'N-85°44'W

RNAV (GPS) RWY 29