

APP CRS
170°

Rwy Idg 10000
TDZE 485
Apt Elev 501

RNAV (RNP) Z RWY 17R

LOUISVILLE MUHAMMAD ALI INTL (SDF)

RNP AR APCH. RF required.

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C. For inop ALS, increase RNP 0.30 all Cats visibility to 1 1/2 SM. Simultaneous approach authorized, except for arrivals at KAEDN, ALANB, and COBLR.

MALSR
A5

MISSED APPROACH: Climb to 3000 on track 170° to TEYUD right turn to JIPAD and on track 292° to NADDI and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
-------------------	-------------------------------------	---------------------------------	------------------------	-------------------------	-------

The main chart displays the RNAV (RNP) Z RWY 17R approach. Key features include:

- Arrival Paths:** From the northwest, paths lead through waypoints like YUNDV, ALANB, and COBLR to the runway. Altitudes range from 4000 to 3600 feet.
- Departure Paths:** From the runway, paths lead to waypoints like TEYUD, JIPAD, and NADDI. Altitudes range from 1067 to 1350 feet.
- Obstacles:** Numerous obstacles are marked with their MSL altitudes, such as 1965, 3600, 2500, 1031, 770, 538, 706, 1159, 840, 1177, 1254, 1304, 923, 644, 1349, and 1350.
- Navigation Aids:** A MALSR (A5) is located near the runway. A VORTAC (A5) is located near the runway.
- MSA:** A Minimum Safe Altitude (MSA) circle is shown with a radius of 25 NM and a minimum altitude of 3600 feet.
- Other Waypoints:** SPYRS, ANEZO, WONEM, STYKR, and KAEDN are also shown.

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 64).

3000

TEYUD

JIPAD

tr 292°

NADDI

CHRCL

2500

2500

170°

RW17R

See planview for multiple IF locations.

This diagram shows a detailed view of the RNAV glidepath. It starts at a 2500-foot altitude on a 170-degree track and descends to the runway. The glidepath is defined by a 3.00-degree angle and a 50-foot threshold crossing height (TCH). The distance from the start of the glidepath to the runway is 6.2 NM.

CATEGORY	A	B	C	D
RNP 0.30 DA	974/60	489 (500-1)		

AUTHORIZATION REQUIRED

ELEV 501

TDZE 485

This diagram shows a detailed view of the runway and taxiway. It includes the runway (RWY 17R), taxiway (TWX 17R), and various navigation aids. The runway length is 11887 feet. The taxiway length is 11887 feet. The runway width is 150 feet. The taxiway width is 150 feet. The runway is marked with 17L, 17R, 35L, and 35R. The taxiway is marked with 17L, 17R, 35L, and 35R.

HIRL all Rwy's

TDZ/CL Rwy's 17L, 17R, 35L and 35R

SE-1, 21 MAR 2024 to 18 APR 2024

SE-1, 21 MAR 2024 to 18 APR 2024

LOUISVILLE, KENTUCKY

Orig-D 15AUG19

LOUISVILLE MUHAMMAD ALI INTL (SDF)

38°10'N-85°44'W

RNAV (RNP) Z RWY 17R