

ILS or LOC RWY 19R

LOC I-CWX 109.9	APCH CRS 188°	Rwy ldg 19R 12.000 19L 12.007 TDZE 19R 1372 19L 1365 Arpt Elev 1372
---------------------------	-------------------------	--

[USAF]

MC CONNELL AFB (KIAB)


RADAR or DME required

- ▼ *When ALS inop, increase RVR to 40 and vis to 3/8 mile.
**When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 3/8 miles.
*** Circling not authorized W of Rwy 1L-19R.




MISSED APPROACH: Climb to 4000 via IAB TACAN R-191 to 15 DME (JILOR). Expect further clearance from ATC.


D-ATIS 124.65 269.9	WICHITA APP CON 134.8 269.1	TOWER 127.25 291.775	GND CON 118.0 275.8
-------------------------------	---------------------------------------	--------------------------------	-------------------------------



EMERG SAFE ALT 100 NM 4000



CATEGORY	A	B	C	D	E
S-ILS 19R *	1572/24		200	(200-1/2)	
S-LOC 19R **	1820/24	448 (500-7%)	1820/45	448	(500-7%)
SIDESTEP 19L	1820/55	455 (500-1)	1820-13/8	455	(500-13/8)
*** CIRCLING	1900-1	528 (600-1)	1900-1 1/2	528 (600-1 1/2)	2400-3 1028 (1100-3)



HIRL all rwys	FAF to MAP 4.4 NM				
Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

ILS or LOC RWY 19R

NC-2, 21 MAR 2024 to 18 APR 2024

NC-2, 21 MAR 2024 to 18 APR 2024