

ILS or LOC RWY 31

LOC I-BNN
108.3

APCH CRS
308°

Rwy Idg
8196

TDZE
4270

Arprt Elev
4295

AL-512 [USAF]

CANNON AFB (KCVS)

ATC RADAR or DME required.

SSALR
(A3)

† MISSED APPROACH: Climb to 6000 out CVS TACAN R-306 to 5.5 DME (LERAY) then turn left climbing to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.

ATIS
119.1 269.9

CANNON APP CON
118.425 352.1

CANNON TOWER
120.4 270.25

GND CON
121.9 275.8

CLNC DEL
120.2 293.225

** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 ½ miles.

† Missed approach requires use of RNAV or ATC radar monitoring.

EMERG SAFE ALT 100 NM 9000

6000
↑
LERAY CVS R-306
5.5

7000
↖
CLINK CVS R-193
12

VGSI TCH (41') and the procedure TCH (51') is greater than 3'.

FOBUR 12

TACAN

JATLA 5.6

308°

6000

5900

GS 3.00° TCH 51

4.9 NM

CATEGORY	A	B	C	D	E
S-ILS 31*	4470-½		200	(200-½)	
S-LOC 31**	4660-½ 390 (400-½)		4660-5⁄8		390 (400-5⁄8)
CIRCLING	4840-1 545 (600-1)		4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)

ELEV 4295

TDZE 4270

HIRL all rwy's

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

CLOVIS, NEW MEXICO

34°23'N-103°19'W

CANNON AFB (KCVS)

Amdr 4 16AUG18

ILS or LOC RWY 31

SW-1, 21 MAR 2024 to 18 APR 2024

SW-1, 21 MAR 2024 to 18 APR 2024