

WAAS CH 51219 W30A	APCH CRS 298°	Rwy Idg 4794 TDZE 352 Arpt Elev 376
--------------------------	------------------	---

AL-6315 (USA)

MACKALL AAF (KHFF)

RNP APCH-GPS	
--------------	--

RADAR required when special use space active.

T * When tower closed, increase vis to 1 mile.

MISSED APPROACH: Climb to 2400 direct AAMMO and hold.

D-ATIS
141.4

FAYETTEVILLE APP CON/DEP CON
127.8 343.725

TOWER★
121.0 (CTAF) 0 254.

GND CON	
128.35	251.05

** Circling NA to RWYs 4, 16, 22, and 34. 689

A531

RWY 30 helicopter visibility reduction below 3/4 mile NA.

Baro-VNAV NA when using
Simmons AAF altimeter setting.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

When local altimeter setting not recieved, use Simmons AAF altimeter setting.

VDP NA with Simmons
altimeter setting.

Additional restrictions are in effect when restricted areas are active.

2400	AAMMO
	

ELEV	376
------	-----

TDZE 352

LENRD HITIT Holding Pattern

298° 118° 298°

2100 2100 2100

GP 3.00°
TCH 55

CATEGORY	A	B	C	D
LPV DA*	602-¾	250	(300-¾)	
LNAV/VNAV DA	793-1⅝	441	(500-1⅝)	
LNAV MDA	760-1 408 (400-1)	760-1⅝ 408 (400-1⅝)		
C CIRCLING**	860-1 484 (500-1)	880-1 504 (600-1)	980-1¼ 604 (700-1¼)	1040-2 664 (700-2)
SIMMONS AAF ALTIMETER SETTING MINIMUMS				
LPV DA	686-1	334	(400-1)	
LNAV/VNAV DA	860-1⅝	508	(500-1⅝)	
LNAV MDA	860-1 508 (500-1)	860-1⅝ 508 (500-1⅝)		
C CIRCLING**	960-1 584 (600-1)	980-1 604 (700-1)	1080-2 704 (800-2)	1140-2½ 764 (800-2½)

CAMP MACKALL, NORTH CAROLINA

35°02'N - 79°30'W

MACKALL AAF (KHFF)

Amdt 1 07SEP23

RNAV (GPS) RWY 30

SE-2, 21 MAR 2024 to 18 APR 2024

SE-2, 21 MAR 2024 to 18 APR 2024