

LOC/DME I-EFE	APP CRS	Rwy Idg	7002
109.35	179°	TDZE	576
Chan 30 (Y)		Apt Elev	589

ILS or LOC RWY 18

MCKINNEY NTL (TKI)

DME required for procedure entry.
DME required.

VDP NA when using Dallas Love Fld altimeter setting. When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA 70 feet and all MDA 80 feet, increase S-LOC 18 Cats C/D visibility 1/8 SM, increase Circling visibility Cat C 1/2 SM, Cat D 1/4 SM. For inop ALS, increase S-LOC 18 Cats C/D visibility to 1 SM. For inop ALS when using Dallas Love Fld altimeter setting, increase S-ILS 18 all Cats visibility to 1/8 SM and increase S-LOC 18 Cats C/D to 1 1/4 SM.

MALSR

MISSED APPROACH:
Climb to 1500 then climbing left turn to 2400 on heading 360° and on TTT VOR/DME R-042 to BRDJE/TTT 41.5 DME and hold.

ATIS 119.925	REGIONAL APP CON 124.3 282.275	MC KINNEY TOWER ★ 118.825 (CTAF) 0	GND CON 121.875	CLNC DEL 121.35 (When twr closed)	UNICOM 122.95
-----------------	-----------------------------------	---------------------------------------	--------------------	---	------------------

ALTERNATE MISSED APCH FIX

BONHAM
BYP
114.6
Chan 93

LOCALIZER 109.35
I-EFE
Chan 30 (Y)

BONHAM
114.6 BYP
Chan 93

(CFBHF)

ELEV 589

TDZE 576

179° 4.6 NM from FAF

HIRL Rwy 18-36

1500

2400

TTT R-042

BRDJE TTT 41.5

JIPUK I-EFE 6.2

Remain within 10 NM

*LOC only.

CATEGORY	A	B	C	D
S-ILS 18	776-1/2 200 (200-1/2)			
S-LOC 18	920-1/2 344 (400-1/2)	920-5/8 344 (400-5/8)		
CIRCLING	1040-1 451 (500-1)	1120-1 531 (600-1)	1200-1 3/4 611 (700-1 3/4)	1380-2 1/2 791 (800-2 1/2)

DALLAS, TEXAS
Amdt 6A 26MAR20

33°11'N-96°35'W

MCKINNEY NTL (TKI)
ILS or LOC RWY 18

SC-2, 21 MAR 2024 to 18 APR 2024