


APP CRS 064°	Rwy Idg	5001
	TDZE	143
	Apt Elev	150

RNAV (GPS) RWY 6
GEORGE DOWNER (AIV)

NA	DME/DME RNP-0.3 NA. Use Tuscaloosa Nil altimeter setting; when not received, use Columbus/W Point/Starkville altimeter setting and increase all MDA 20 feet, and Circling Cat C visibility ¼ mile. Procedure NA at night. Helicopter visibility reduction below 1 SM NA.	MISSED APPROACH: Climb to 3000 direct CIKOB and hold.

TCL ASOS 132.825	COLUMBUS APP CON 135.6 323.275	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



Visual Segment - Obstacles.				
4 NM Holding Pattern				
3000 ← 244° 064° →				
ZESLO				
JOGAM				
UDLEQ 2.6 NM to RW06				
RW06				
6.4 NM 3 NM 2.6 NM				
CATEGORY	A	B	C	D
LNAV MDA	640-1	497 (500-1)	640-1 3/8	497 (500-1 3/8)
CIRCLING	720-1	570 (600-1)	820-1 3/4 670 (700-1 3/4)	900-2 1/2 750 (800-2 1/2)

