TEDD FIVE DEPARTURE (RNAV)
(TEDDD5.TEDDD) 18312
AL-360 (FAA)
ST LOUIS LAMBERT INTL (STL)
ST. LOUIS, MISSOURI

TEDD FIVE DEPARTURE (RNAV)
(TEDDD5.TEDDD) 19JUL18
ST LOUIS LAMBERT INTL (STL)
ST. LOUIS, MISSOURI

TOP ALTITUDE: 5000

TAKEOFF MINIMUMS
Rwys 6, 24: Standard with minimum climb of 500′ per NM to 1120 then minimum climb of 280′ per NM to 5000.
Rwys 11, 12L/R: Standard with minimum climb of 500′ per NM to FUNKE.
Rwy 29: Standard with minimum climb of 500′ per NM to DSAPP.
Rwys 30L/R: Standard with minimum climb of 500′ per NM to WOLTR.

D-ATIS
125.025 379.925
CLNC DEL
119.5 363.1
CPDLC
GND CON
121.9 348.6 (Inbound)
121.65 377.175 (Outbound)
118.925 227.125 (Rwy 11/29)
ST. LOUIS TOWER
120.05 284.6 (Rwys 12L/30R, 24)
118.5 257.7 (Rwy 12R/30L)
132.475 239.275 (Rwys 6, 11/29)
ST. LOUIS DEP CON
119.15 335.5

NOTE: RNAV 1.
NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required.
NOTE: For use by turbojet aircraft only.



NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)