

APP CRS
016°

Rwy Idg
TDZE
Apt Elev
5700
56
56

RNAV (RNP) Z RWY 2L

JOHN WAYNE/ORANGE COUNTY (SNA)

For uncompensated Baro-VNAV systems, procedure NA below 5°C (41°F) or above 54°C (130°F). GPS required.

MISSED APPROACH: Climb to 800 then climbing left turn to 2600 direct SLI VORTAC and hold.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 0 343.625	GND CON 120.8	CLNC DEL 118.0	CPDLC	UNICOM 122.95
------------------------	-------------------------------------	--	-------------------------	--------------------------	-------	-------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).

NEWPO

1600

GP 3.00°
TCH 55

See planview for multiple IF locations.

4.7 NM

800 2600 SLI

CATEGORY

A B C D

RNP 0.30 DA

403-1 3/8 347 (400-1 3/8)

AUTHORIZATION REQUIRED

ELEV 56 TDZE 56

SANTA ANA, CALIFORNIA
Orig 10NOV16

JOHN WAYNE/ORANGE COUNTY (SNA)
33°41'N-117°52'W

RNAV (RNP) Z RWY 2L