

VOR/DME OTK	APP CRS	Rwy Idg	8002
114.8	338°	TDZE	200
Chan 95		Apt Elev	203


VOR RWY 36
VALDOSTA RGNL (VLD)

V **A** Rwy 36 helicopter visibility reduction below ¾ SM NA. For inop ALS, increase S-36 Cats A/B visibility to 1 SM and Cats C/D to 1½ SM; ASMUC FIX MINIMUMS: increase S-36 all Cats visibility to 1 SM.




MISSED APPROACH: Climb to 1200 then climbing left turn to 2000 direct OTK VOR/DME and hold, continue climb-in-hold to 2000.

ASOS	VALDOSTA APP CON *	VALDOSTA TOWER *	GND CON	UNICOM
126.225	126.6 285.6	128.35 (CTAF) 0	121.7	122.95



ELEV 203	TDZE 200
----------	----------



1200	2000	OTK					
CATEGORY				A	B	C	D
S-36				780-¾	580 (600-¾)	780-1¼	580 (600-1¼)
CIRCLING				780-1	577 (600-1)	900-2 697 (700-2)	1020-2¾ 817 (900-2¾)
ASMUC FIX MINIMUMS							
S-36				580-¾ 380 (400-¾)			
CIRCLING				640-1 437 (500-1)	700-1 497 (500-1)	900-2 697 (700-2)	1020-2¾ 817 (900-2¾)