LOC/DME I-ASX	APP CRS	Rwy Idg 5197
109.3	023°	TDZE 826
Chan 30		Apt Elev 827

LOC RWY 2

JOHN F KENNEDY MEML (ASX)

DME required.

T NA Rwy 2 helicopter visibility reduction below ¾ SM NA. VDP NA when using Ironwood altimeter setting. When local altimeter setting not received, use Ironwood altimeter setting and increase all MDA 140 feet; increase S-02 Cat C/D visibility ⅜ SM and Circling Cat C/D visibility ½ SM.

MISSED APPROACH: Climb to 2200 then climbing right turn to 3500 on IWD VOR/DME R-280 to CEVLU/ IWD 20 DME and hold.

ASOS	MINNEAPOLIS CENTER	GCO	UNICOM
126.775	126.45 276.4	122.25	122.8 (CTAF) L







CATEGORY	A	B	C	D
S-2	1200-1	374 (400-1)	1200-1⅛	374 (400-1⅛)
C CIRCLING	1240-1 413 (500-1)	1280-1 453 (500-1)	1440-1¾ 613 (700-1¾)	1560-2¼ 733 (800-2¼)

REIL Rwy 2 L
MIRL Rwys 2-20 and 13-31 L

EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024