

22363

RNAV (GPS) RWY 15

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 47°C. Rwy 15 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Hancock County-Bar Harbor altimeter setting: increase LPV DA to 462 feet and all visibilities $\frac{3}{4}$ SM; increase LNAV/VNAV DA to 565 feet and all visibilities $\frac{1}{2}$ SM; increase all MDA 160 feet and LNAV visibility Cat C and D $\frac{3}{4}$ SM and Circling visibility Cat C and D $\frac{1}{2}$ SM. Baro-VNAV NA when using Hancock County-Bar Harbor altimeter setting. Straight-in Rwy 15 NA at night, Circling Rwy 15 NA at night.

MISSED APPROACH:
Climb to 500 then
climbing right turn to
4000 direct PIERR
and hold, continue
climb-in-hold to 4000.

UNICOM
122.8 (CTAF) 

ELEV 45

TDZE 44

△ 250±

145°

0.3% UP

4002 X 75

15 33

MIRL Rwy 15-33 **L**

REIL Rwys 15 and 33 **L**

EASTPORT MUNI (EPM)
RNAV (GPS) RWY 15