

WAAS CH 66100 W13A	APP CRS 132°	Rwy Idg 12803 TDZE 1065 Apt Elev 1078
--	------------------------	--


RNAV (GPS) RWY 13

TOPEKA RGNL (FOE)

⚠ If local altimeter setting not received, use Philip Billard Muni altimeter setting and increase all DAs/MDAs 60 feet. Baro-VNAV and VDP NA when using Philip Billard Muni altimeter setting. Baro-VNAV NA below -17°C (2°F). DME/DME RNP-0.3 NA. Inoperative table does not apply to LPV, LNAV/VNAV and LNAV Cat C.

MISSED APPROACH: Climb to 3000 direct ERJAG and hold.


ATIS 128.25	KANSAS CITY CENTER 123.8 343.7	FORBES TOWER* 120.8 (CTAF) 340.2	GND CON 121.7 275.8	UNICOM 122.95
-----------------------	--	--	-------------------------------	-------------------------




NC-2, 02 MAR 2017 to 30 MAR 2017

NC-2, 02 MAR 2017 to 30 MAR 2017

ELEV 1078	D	TDZE 1065
-----------	----------	-----------



REIL Rwy 3, 13 and 21
MIRL Rwy 3-21
HIRL Rwy 13-31



CATEGORY	A	B	C	D
LPV DA		1315-¾	250 (300-¾)	
LNAV/VNAV DA		1505-1½	440 (500-1½)	
LNAV MDA	1540-¾	475 (500-¾)	1540-1¼ 475 (500-1¼)	1540-1½ 475 (500-1½)
C CIRCLING	1540-1 462 (500-1)	1580-1 502 (600-1)	1580-1½ 502 (600-1½)	1700-2 622 (700-2)