

MUELR FOUR DEPARTURE (RNAV)

AL-237 (FAA)

LOS ANGELES INTL (LAX)
LOS ANGELES, CALIFORNIA

D-ATIS DEP
135.65
CLNC DEL
120.35 327.0
CPDLC
GND CON
(N) 121.65 327.0
(S) 121.75 327.0
(W) 121.4 327.0
LOS ANGELES TOWER
(N) 133.9 239.3
(S) 120.95 379.1
SOCAL DEP CON
124.3 363.2 (045°-224°)
125.2 263.023 (225°-044°)



TAKEOFF MINIMUMS
Rwys 6L/R, 7L/R: NA-ATC.
Rwys 24L/R, 25L/R: Standard with minimum climb
of 500' per NM to 640.

NOTE: DME/DME/IRU or GPS required.
NOTE: RADAR required.
NOTE: RNAV 1.
NOTE: Turbojets only.
NOTE: Maintain at or below 250K unless otherwise directed by ATC.

TOP ALTITUDE:
10000

SAN MARCUS

RZS

10000
288°
(24)

SCHOR

10000
288°
(9)

10000

273°
(16)

WGGNR

10000
289°
(11)

IKAYE

10000
342°
(10)

FIXIT

10000 290K

289°
(7)

MUELR

253°
(11)

NAANC

253°
(7)

ENNEY

5000
1300

256°
(2)

DIREY

3000

251°

640

251°

DOCKR

3000

252°

256° (2)

EVOSE

5000
1300

257° (12)

MKGEE

252° (6)

HIPR

3000

251°

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

MUELR FOUR DEPARTURE (RNAV)