LOC I-SHD	APP CRS	Rwy Idg	6002
109.5	047°	TDZE	1184
		Apt Elev	1201

AL-5369 (FAA)

ILS or LOC RWY 5

SHENANDOAH VALLEY RGNL (SHD)

ADF Required. Autopilot coupled approach NA below 1494 feet. When local altimeter setting not received, use Charlottesville altimeter setting and increase all DA 130 feet, all MDA 140 feet. Increase ILS visibility ¼ mile all Cats, LOC visibility Cat C/D ¼ mile and Circling Cat D ½ mile. For inoperative MALSR when using Charlottesville altimeter setting, increase ILS visibility to 1¼ miles.

- 23°C/-9°F

MALSR

MISSED APPROACH: Climb to 2600 then climbing left turn to 3600 direct SH LOM and hold.

AWOS-3	POTOMAC APP CON	CLNC DEL	UNICOM
124.925	132.85 323.125	118.35	123.0 (CTAF) L



CATEGORY	A	B	C	D
S-ILS 5	1384-½ 200 (200-½)			
S-LOC 5	1620-½ 436 (500-½)		1620-¾ 436 (500-¾)	1620-1 436 (500-1)
CIRCLING	1620-1 419 (500-1)	1660-1 459 (500-1)	1660-1½ 459 (500-1½)	1820-2 619 (700-2)

FAF to MAP 4.2 NM					
Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

NE-3, 04 JAN 2018 to 01 FEB 2018
NE-3, 04 JAN 2018 to 01 FEB 2018