APP CRS	Rwy Idg	9748
071°	TDZE	116
	Apt Elev	128

RNAV (RNP) Z RWY 6R

LOS ANGELES INTL (LAX)

For uncompensated Baro-VNAV systems, procedure NA below 5°C (41°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 3000 on track 071° to ZIMLO and on track 042° to AMTRA and hold.

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON	CLNC DEL	CPDLC
ARR 133.8 DEP 135.65	124.3 363.2 (APCH FM WEST) 124.9 269.0 (090°-224°) 124.5 235.975 (225°-044°) 128.5 360.7 (045°-089°)	N 133.9 239.3 S 120.95 379.1	N 121.65 327.0 S 121.75 327.0 W 121.4 327.0	120.35 327.0	

MISSED APCH FIX

AMTRA 049° 229° 4 NM

1168 1870 2126 2824 2908 866 1387 649 299 462 587

1000 2000

Santa Monica Muni

RADAR required for procedure entry at SASSI.

(IAF) WAKER 6000 210K

5600 142° (3)

KILIE

3600 104° (8.5)

OVBIE

3600 (6.7)

5800 251° (4)

(IAF) SASSI 7000 210K (RF REQD)

1800 071° (6)

(FAF) GUPPI

071° (5.1)

RW06R

(5.9) 071°

042° (11.6)

ZIMLO

293

KRSPI

3600 071° (4.9)

(IF) OTTES

(IAF) EXERT

4000 053° (5.1)

Procedure NA for arrivals at EXERT on V25 westbound and V27 northwest bound.

MSA RW06R 25 NM

7800

ELEV 128 D TDZE 116

071° to RW06R

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

3000	ZIMLO	tr	AMTRA
tr 071°		042°	

OTTES 3600 071° GUPPI 1800 RW06R 1800

GP 3.00° TCH 53

6 NM 5.1 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	471/40	355 (400-¾)		

AUTHORIZATION REQUIRED

TDZ/CL Rwys 6R, 7L, 24R, and 25L HIRL all Rwys

SW-3, 28 MAR 2019 to 25 APR 2019
SW-3, 28 MAR 2019 to 25 APR 2019