

# LUFKIN TWO DEPARTURE

ATIS  
135.575 269.9  
GND CON  
121.6 275.8  
ELLINGTON TOWER  
126.05 253.5  
HOUSTON DEP CON  
134.45 284.0

**TOP ALTITUDE:  
ASSIGNED BY ATC**

LITTLE ROCK
113.9 LIT
Chan 86
N34°40.66'
W92°10.83'
L-18, H-6

NOTE: RADAR and DME required.  
NOTE: For aircraft destined LIT or  
overflying LIT or PXV.

LUFKIN
112.1 LFK
Chan 58
N31°09.75'
W94°43.01'

SKKIP  
N31°14.91'  
W94°39.45'

SUSHI  
N30°35.48'  
W95°04.39'

COLET  
N30°26.96'  
W95°09.66'

KYANN  
N30°15.53'  
W95°13.96'

HUMBLE
116.6 IAH
Chan 113

DAISETTA
116.9 DAS
Chan 116

### TAKEOFF MINIMUMS

Rwys 4, 17L/R, 35L/R: Standard.

Rwy 22: 200-1¼ or standard with minimum climb  
of 214' per NM to 300 or alternatively with  
standard takeoff minimums and a normal  
200' per NM climb gradient, takeoff must  
occur no later than 1400' prior to DER.



NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

# LUFKIN TWO DEPARTURE