

LURIC SEVEN DEPARTURE (RNAV)

ATIS
135.575 269.9
GND CON
121.6 275.8
ELLINGTON TOWER
126.05 253.5
HOUSTON DEP CON
134.45 284.0

TOP ALTITUDE: ASSIGNED BY ATC

NOTE: RADAR required.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.

TAKEOFF MINIMUMS

Rwys 4, 17L/R, 22, 35L/R:
Standard with minimum
climb of 500' per NM to 540.




DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 4: Climb heading 039° to 540 for
RADAR vectors to KNTKY, then
TAKEOFF RWYS 17L/R: Climb heading 174° to 540
for RADAR vectors to KNTKY, then
TAKEOFF RWY 22: Climb heading 219° to 540 for
RADAR vectors to KNTKY, then
TAKEOFF RWYS 35L/R: Climb heading 354° to 540
for RADAR vectors to KNTKY, then

. . . . on track 032° to PEETY, then on track 032° to
DARTR, then on track 031° to MUSIQ, then on track
031° to CLAVN, then on track 031° to VELCO, then
on track 031° to ENJOY, then on track 031° to LURIC, then
on (transition). Maintain ATC assigned altitude.
Expect filed altitude 10 minutes after departure.

HAWES TRANSITION (LURIC7.HAWES)

ORRTH TRANSITION (LURIC7.ORRTH)



NOTE: Chart not to scale.

SC-5, 12 SEP 2019 to 10 OCT 2019

SC-5, 12 SEP 2019 to 10 OCT 2019

LURIC SEVEN DEPARTURE (RNAV)