LOC/DME I-ARK	APP CRS	Rwy Idg 9000
110.95	185°	TDZE 90
Chan 46 (Y)		Apt Elev 96

ILS RWY 17L (CAT II)
ORLANDO INTL (MCO)

Simultaneous approach authorized. DME or RADAR required. Bright lights on highway midway between Rwy 17L and Rwy 17R may be mistaken for runway lights.

ALSF-2

MISSED APPROACH: Climb to 500 then climbing left turn to 3000 on heading 100° and ORL VORTAC R-140 to PRESK INT/ORL 16.2 DME and hold.

D-ATIS	ORLANDO APP CON	ORLANDO TOWER	GND CON	CLNC DEL	
ARR 121.25	124.8 307.0	124.3 (Rwys 18L-36R,18R-36L) 253.5	126.4 275.8 (East)	134.7	CPDLC
DEP 120.525		118.45 (Rwys 17L-35R,17R-35L) 253.5	121.8 275.8 (West)	341.7	

RADAR REQUIRED

(IAF) KAKEY I-ARK 17 RADAR

(IF) HERVI I-ARK 13.8 RADAR

FONIK I-ARK 10.7 RADAR

SEEDO I-ARK 9.1 RADAR

COCAS I-ARK 5.9 RADAR

IM

PRESK INT ORL 16.2

005° 185° 185° 185° (3.2) (3.2) (3.2) 4000 3000 1500

2500 185° (1.6)

ORLANDO 112.2 ORL Chan 59

Executive

1749± 1749

ALTERNATE MISSED APCH FIX
PRESK INT MLB 30
R-305 125° R-065 305° 116.0 LAL Chan 107 110.0 MLB Chan 37

MSA ORL 25 NM 3000

238 215 353 464 214 346 549

R-ORL R-140

LOCALIZER 110.95 I-ARK Chan 46(Y)

116.0 LAL R-065 Chan 107 140° 320°

ELEV 96 D TDZE 90



HIRL all Rwys
REIL Rwy 36L
TDZ/CL Rwys 17L/R, 18R, 35L/R and 36R

500	3000 hdg 100°	ORL R-140	PRESK △

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).



CATEGORY	A	B	C	D
S-ILS 17L	RA 101/12 100 DA 190			

CATEGORY II ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

SE-3, 10 OCT 2019 to 07 NOV 2019
SE-3, 10 OCT 2019 to 07 NOV 2019