LOC I-HEZ	APP CRS	Rwy Idg	6500
111.35	136°	TDZE	266
		Apt Elev	272

ILS or LOC RWY 13

HARDY-ANDERS FIELD NATCHEZ-ADAMS COUNTY (HEZ)

When local altimeter setting not received, use Vicksburg Tallulah Rgnl altimeter setting; increase DA to 599 feet and all visibilities ⅛ mile; increase all MDA 140 feet and S-LOC 13 Cat C and D visibility ½ mile, Circling Cat C/D visibility ¼ mile. For inop MALSR, when using Vicksburg Tallulah Rgnl altimeter setting, increase S-ILS 13 visibility all Cats to 1⅛ miles.

NA

MALSR

MISSED APPROACH: Climb to 2000 then left turn direct HEZ VOR/DME and hold.

AWOS-3PT	HOUSTON CENTER	UNICOM
124.675	120.975 299.6	122.8 (CTAF) L

ALTERNATE MISSED APCH FIX

002° 182°

NATCHEZ-ADAMS CO 388 HAH

(IF) CASDU HEZ 11.4

316°

091° 271°

1900 NoPT HEZ 11.4 Arc

LR-323

LR-302

1900 136° (6.1)

(IAF) ZUTKI INT HEZ 5.3

NATCHEZ-ADAMS CO 388 HAH

(IAF) NIFSO HEZ 11.4

R-044

082°

588

1900 to ZUTKI 312° (5.3)

852

1105

1900 NoPT HEZ 11.4 Arc

NATCHEZ 110.0 HEZ Chan 37

133°

313°

622 440 423

500

728

R-248

R-133

MSA HEZ 25 NM

2200

(IAF) NIFTE HEZ 11.4

LOCALIZER 111.35 I-HEZ

840

ADF or DME REQUIRED

ELEV 272 TDZE 266

136° 5 NM from FAF

5

A5

6500 X 150

5000 X 150

81

353

36

31

HIRL Rwy 13-31

MIRL Rwy 18-36 L

Remain within 10 NM

ZUTKI INT HEZ 5.3

2000

HEZ

316°

1900

CASDU HEZ 11.4

1900 136°

HEZ 0.4

GS 3.00° TCH 54

1900

6.1 NM 5 NM

CATEGORY	A	B	C	D
S-ILS 13	466-½ 200 (200-½)			
S-LOC 13	700-½ 434 (500-½)		700-¾ 434 (500-¾)	
CIRCLING	740-1 468 (500-1)	800-1 528 (600-1)	800-1½ 528 (600-1½)	840-2 568 (600-2)

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

SC-4, 10 OCT 2019 to 07 NOV 2019

SC-4, 10 OCT 2019 to 07 NOV 2019