


HOODO SIX DEPARTURE (RNAV)

SC-5, 10 OCT 2019 to 07 NOV 2019

ATIS
119.525
CLNC DEL
121.725

EXECUTIVE TOWER *
122.975 (CTAF)
HOUSTON DEP CON
123.8 257.7

NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: ATC assigned only.
NOTE: DME/DME/IRU or GPS required.
NOTE: For non-GPS equipped aircraft, LCH, ILA, TBD, and LEV DME's must be operational.



SCHOLES
VUH



HOODO

SBIRD

CFOOD

BOWFN


LEEVILLE

HARVEY

TAKEOFF MINIMUMS

Rwy 18, 36: Standard with a minimum climb of 500' per NM to 680.

TOP ALTITUDE: ASSIGNED BY ATC



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF Rwy 18: Climb heading 175° to 680, for RADAR vectors to VUH VOR/DME, thence
TAKEOFF Rwy 36: Climb heading 355° to 700, for RADAR vectors to VUH VOR/DME, thence

. . . . on track 118° to HOODO, then on (transition). Maintain ATC assigned altitude.
Expect filed altitude 10 minutes after departure.

- BOWFN TRANSITION (HOODO6.BOWFN)
- CFOOD TRANSITION (HOODO6.CFOOD)
- HARVEY TRANSITION (HOODO6.HRV)
- LEEVILLE TRANSITION (HOODO6.LEV)
- SBIRD TRANSITION (HOODO6.SBIRD)

SC-5, 10 OCT 2019 to 07 NOV 2019