ILS or LOC RWY 31

MINOT INTL (MOT)

LOC/DME I-MOT	APP CRS	Rwy Idg	7700
111.9	312°	TDZE	1679
Chan 56		Apt Elev	1716

DME or RADAR required.

For Inop ALS, increase S-ILS 31 Cat E visibility to RVR 4000, and S-LOC 31 Cat C, D and E visibility to RVR 4500. Auto Pilot coupled approach NA below 2060.

MALSR

MISSED APPROACH: Climb to 3700 then left turn direct MOT VOR/DME and hold.

ASOS	MINOT APP CON ★	MAGIC CITY TOWER ★	GND CON	UNICOM
118.725	119.6 363.8	118.2 (CTAF) L 251.125	121.9	122.95





REIL Rwy 13
REIL Rwys 8 and 26 L
HIRL Rwys 8-26 and 13-31 L

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44



CATEGORY	A	B	C	D	E
S-ILS 31	1879/24 200 (200-½)				
S-LOC 31	1980/24 301 (300-½)			1980/40 301 (300-¾)	
CIRCLING	2200-1 484 (500-1)		2240-1½ 524 (600-1½)	2280-2 564 (600-2)	2800-3 1084 (1100-3)

NC-1, 05 NOV 2020 to 03 DEC 2020
NC-1, 05 NOV 2020 to 03 DEC 2020