

ATIS

134.55

CLINC DEL

121.6

GND CON


121.6

ANN ARBOR TOWER \*

120.3 (CTAF)

DETROIT DEP CON

118.95 284.0



TOP ALTITUDE:  
ASSIGNED BY ATC

TAKEOFF MINIMUMS:

Rwys 6, 24: Standard.

Rwys 12, 30: NA - Environmental.



NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: Turboprop departures at/above 10000,

maintain 280K until advised by ATC.

NOTE: BROKK TRANSITION: For use by flights filed at or below

FL270, or as assigned by ATC.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 6: Climb on heading 060° or as assigned for RADAR vectors to cross MALTB at or above 4000, thence....  
TAKEOFF RUNWAY 24: Climb on heading 240° or as assigned for RADAR vectors to cross MALTB at or above 4000, thence....

....on track 094° to HHOWE, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

BROKK TRANSITION (HHOWE3.BROKK)  
LINCON TRANSITION (HHOWE3.LINCON)