

FLYING TEN (See ARCHER on page 83)

FORT DRUM N27°33.00' W80°48.00'
RCO 122.2 (SAINT PETERSBURG RADIO)

MIAMI
L-24F

FORT LAUDERDALE

DOWNTOWN FORT LAUDERDALE HELIPORT (DT1) 0 N UTC-5(-4DT) N26°07.23' W80°08.52'

MIAMI

114 NOTAM FILE MIA

HELIPAD H1: H84X84 (CONC) MIRL

HELIPORT REMARKS: Attended irregularly. For reservations and assistance call 1-954-968-9675. Primary apch 145° true crs inbd. Rooftop fac. PPR to use parking position, all hrs. Ctc Ft Lauderdale/Hollywood Intl twr on freq 119.3 prior to entering Ft Lauderdale Class C airspace and upon tkf. Repetitive flt trng and stu solos discouraged. Noise sensitive areas all quadrants. No tkfs or ldgs at eastern parking position. Parking prohibited on ldg/tkf (western) position. Max gross wt 11,900 lbs. Max rotor diameter 46'.

AIRPORT MANAGER: (954) 828-4968

COMMUNICATIONS: CTAF/UNICOM 123.05

CLEARANCE DELIVERY PHONE: For CD ctc Miami Apch at 305-869-5432.

FORT LAUDERDALE EXEC (FXE)(KFXE) 5 N UTC-5(-4DT) N26°11.84' W80°10.24'

MIAMI
H-81, L-23C, A
IAP, AD

13 B LRA NOTAM FILE FXE

RWY 09-27: H6002X100 (ASPH-GRVD) S-56, D-81

PCN 18 F/A/X/T HIRL

RWY 09: MALS. PAPI(P4L)—GA 3.0° TCH 56'. Tree.

RWY 27: REIL. PAPI(P4L)—GA 3.25° TCH 56'. Bldg.

RWY 13-31: H4000X100 (ASPH-GRVD) S-30, D-60

PCN 26 F/B/X/T MIRL

RWY 13: REIL. PAPI(P2L)—GA 3.25° TCH 44'. Tree.

RWY 31: REIL. PAPI(P2L)—GA 3.25° TCH 50'. Road.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 27	13-31	3000
RWY 31	09-27	3250

SERVICE: S4 FUEL 100LL, JET A, B OX 1, 3

AIRPORT REMARKS: Attended continuously. Flocks of birds on and in/ov arpt. Rwy 13-31 CLOSED 0300-1200Z± when Rwy 09-27 is opr full length. Portions of Rwy 31 run-up area (West of Twy B) are not visible from the twr. Taxilane C (SW of Twy B) is a non-ctld opr area. Req progressive taxi if unfamiliar. All acct opr avoid overflts of residential area one-half mile SW of ctd twr. Rwy 09 nighttime preferential use rwy for all acct arrivals when winds permit. Rwy 27 nighttime preferential use rwy for all acct departures when winds permit. Use caution for drones auth AOB 400' within Class D. PPR for acct in excess of rwy wt bearing capacity. Call arpt mgr Mon-Fri 954-828-4955. Maint engine run-ups prohibited 0000-1200Z±. NS ABTMT procedures in effect. Call arpt mgr 954-828-4955. CSTMS ramp located Twy G7. US CSTMS avbl 1300-0459Z±. US CSTMS ramp clsd to arr acct 0500-1300Z±. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: (954) 828-4968

WEATHER DATA SOURCES: ASOS 119.85 (954) 772-2537. LAWRS.

COMMUNICATIONS: ATIS 119.85 UNICOM 122.95

Ⓜ MIAMI APP/DEP CON 119.7 (Usable 4000' and blo)

TOWER 120.9 **GND CON** 121.75 **CLNC DEL** 127.95

AIRSPACE: CLASS D svc continuous.

RADIO AIDS TO NAVIGATION: NOTAM FILE FLL.

(H) VOR/DME 114.4 FLL Chan 91 N26°04.44' W80°09.99' 004° 7.4 NM to fld. 6/6W.

DME unusable:

030°-040° blo 3,000'

140°-192° blo 2,000'

360°-010° byd 35 NM blo 2,000'

VOR unusable:

140°-192° blo 2,000'

ILS 111.1 I-FXE Rwy 09. Class IT.

