ILS or LOC RWY 9

FLORENCE RGNL (FLO)

LOC I-FLO	APP CRS	Rwy Idg	6502
109.1	089°	TDZE	147
		Apt Elev	147

DME Required. When local altimeter setting not received, use Darlington altimeter setting and increase all DA/MDA 60 feet, increase S-LOC and Circling Cats B/C/D visibility ¼ mile. Night Landing: Rwy 1, 19 NA.

MALSR

MISSED APPROACH: Climb to 600 then climbing left turn to 2000 via heading 070° and FLO VORTAC R-088 to CARLI/FLO 15.9 DME and hold.

ATIS	FLORENCE APP CON★	FLORENCE TOWER★	GND CON	CLNC DEL	UNICOM
123.625	118.6 341.7 (256°-074°) 135.25 316.15 (075°-255°)	125.1 (CTAF) L 353.85	121.9 353.85	121.9 353.85	122.95







CATEGORY	A	B	C	D
S-ILS 9	347-½ 200 (200-½)			
S-LOC 9	840-½ 693 (700-½)		840-1½ 693 (700-1½)	840-1¾ 693 (700-1¾)
CIRCLING	840-1 693 (700-1)		840-2 693 (700-2)	840-2¼ 693 (700-2¼)

REIL Rwys 1,19 and 27 L
HIRL Rwy 9-27 L

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58

SE-2, 25 MAR 2021 to 22 APR 2021
SE-2, 25 MAR 2021 to 22 APR 2021