

O'HARE SIX DEPARTURE

EC-3, 22 APR 2021 to 20 MAY 2021

TOP ALTITUDE:
5000

SPECIAL INSTRUCTIONS: For appropriate departure control frequency, see graphic. Use frequency depicted within the sector where first navaid/fix for your route is located (sectors indicated by dashed lines; frequencies indicated in dashed box outlines).

NOTE: All turbo-jet departures in all directions, maintain 250K until advised by ATC.

CINC DEL 121.6 CPDLC

KEELER
116.6 ELX
Chan 113
N42°08.66'
W86°07.36'
L-28, H-5-10

CHICAGO DEP CON
EAST/NORTH
125.0 337.4

GIPPER
115.4 GJ
Chan 101
N41°46.12'-W86°19.11'
L-28, H-5-10

PETTY
N42°49.64'
W87°38.04'
L-28

BADGER
116.4 BAE
Chan 111
N43°07.01'-W88°17.06'
L-28, H-5

CHICAGO
Chan 19 (Y)
GCO (108.25)
N41°59.65'
W87°54.14'

DUPAGE
108.4 DPA
Chan 21
N41°53.42'
W88°21.01'
L-28

IOWA CITY
116.2 IOW
Chan 109
N41°31.14'
W91°36.80'
L-28, H-5

POLO
111.2 PLL
Chan 49
N41°57.94'
W89°31.45'
L-28

NOONNY
N41°38.84'
W88°52.71'
L-28

MYKIE
N41°59.65'
W87°54.14'

OLINN
N41°59.65'
W87°54.14'

PEKUE
N41°59.65'
W87°54.14'

ACITTO
N40°34.90'-W88°09.86'
L-27, H-5

ROBERTS
116.8 RBS
Chan 115
N40°34.90'-W88°09.86'
L-27, H-5

CHICAGO DEP CON
SOUTH
126.6 25 327.0 75

PEOTONE
113.2 EON
Chan 79
N41°16.18'-W87°47.46'
L-28

RAYNR
N43°07.01'-W88°17.06'
L-28, H-5

PMPKN
N41°59.65'
W87°54.14'

CHICAGO DEP CON
EAST/NORTH
125.0 337.4

MOBILE
N41°46.12'-W86°19.11'
L-28, H-5-10

EBAKE
N42°08.66'
W86°07.36'
L-28, H-5-10

DUFFE
N42°08.66'
W86°07.36'
L-28, H-5-10

- TAKEOFF MINIMUMS**
 Rwy 4L/R: 9L/C/R, 10L/C/R, 22L, 27L, 28C/R: Standard.
 Rwy 22R: NA - ATC.
 Rwy 27C: Standard with minimum climb of 220' per NM to 1800.
 Rwy 27R: Standard with minimum climb of 220' per NM to 1700.
 Rwy 28L: Standard with minimum climb of 210' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1300' prior to DER.

NOTE: RADAR required.
NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

O'HARE SIX DEPARTURE