

KERMIT THREE DEPARTURE

**TOP ALTITUDE:
3000**

ATIS★
133.675
CLNC DEL
118.55
CLNC DEL (when twr closed)
127.25
GND CON
121.85
CONCORD TOWER★
134.65 (CTAF)
UNICOM
122.95
CHARLOTTE DEP CON
128.325 307.8

PULASKI
116.8 PSK
Chan 115
N37°05.26'
W80°42.77'

NALEY
N36°21.16'
W80°48.41'

BARRETTS MOUNTAIN
110.8 BZM
Chan 45

SUGARLOAF MOUNTAIN
112.2 SUG
Chan 59

CHARLOTTE
115.0 CLT
Chan 97
N35°11.42'
W80°57.11'

RALEIGH/DURHAM
117.2 RDU
Chan 119

JOTTA
N36°00.88'
W80°50.96'
L-25
2200
8000
4000
110
137
70
120
110

MERIL
N35°36.79'
W79°26.03'
L-36
8000
4100
076
791

SANDHILLS
111.8 SDZ
Chan 55

BOBZY
N35°11.13'
W81°38.05'
2900
275
8000
3600
119

NEANO
N35°04.88'
W81°59.79'
L-25
250
8000
3600
119

DEBIE
N34°55.82'
W81°48.53'
2700
255
11000
2700
45

WALUT
N34°40.00'
W80°50.53'
R-275
5000
2700
175
32
2000
119
51

LILLS
N34°56.13'
W79°55.81'
L-25-35-36
9000
2700
112
53

FOOTHILLS
113.4 ODF
Chan 81

ANDYS
N34°22.25'
W81°08.63'
L-24-25
8000
2300
196
79

HAMLN
N34°21.54'
W80°46.71'
H-12
2100
196
79

CHESTERFIELD
108.2 CTF
Chan 19

TREAL
N33°04.18'
W81°26.46'
H-9-12
129

- NOTE: For turbojet aircraft only.
- NOTE: RADAR and DME required.
- NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.
- NOTE: Transponder code will be issued via Concord ATCT or Charlotte clearance delivery.

TAKEOFF MINIMUMS

Rwy 2: Standard.
Rwy 20: 300-13/4 or standard with minimum climb of 204' per NM to 1000.
Or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1200' prior to DER.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SE-2, 22 APR 2021 to 20 MAY 2021

SE-2, 22 APR 2021 to 20 MAY 2021