


# WEAZL FOUR DEPARTURE (RNAV)

CONCORD, NORTH CAROLINA

**TOP ALTITUDE:**  
**3000**

- ATIS ★ 133.675
- CLNC DEL 118.55
- CLNC DEL (when twr closed) 127.25
- GND CON 121.85
- CONCORD TOWER ★ 134.65 (CTAF)
- UNICOM 122.95
- CHARLOTTE DEP CON 128.325 307.8



### TAKEOFF MINIMUMS

Rwy 2: Standard.  
 Rwy 20: Standard with minimum climb of 320' per NM to 2400.

- NOTE: For turbojets only.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.
- NOTE: RADAR required.
- NOTE: If unable to accept climb rates, advise ATC on initial contact.
- NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

NOTE: Chart not to scale.



### DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 2: Climb heading 016° to 2200, thence...

TAKEOFF RWY 20: Climbing left turn heading 150° to 2400, thence. . . .

. . . on heading assigned by ATC, expect RADAR vectors to WHFRD, then on track 003° to WEAZL, then on CLAWD transition. Maintain 3000, expect clearance to filed altitude within 10 minutes after departure.

CLAWD TRANSITION (WEAZL4.CLAWD)

# WEAZL FOUR DEPARTURE (RNAV)