


LOS ANGELES

LOS ANGELES INTL (LAX)(KLAX) P (AF CG) 9 SW UTC-8(-7DT) 128 B LRA Class I, ARFF Index E NOTAM FILE LAX
RWY 07L-25R: H12923X150 (CONC-GRVD) S-175, D-225, 2D-400, 2D/2D2-900 PCN 70 R/A/W/T HIRL CL
RWY 07L: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 83'. RVR-TMR Thld dspcd 832'. Rgt tfc.
RWY 25R: MALSR. PAPI(P4L)—GA 3.0° TCH 75'. RVR-TMR Thld dspcd 957'. Railroad. 0.3% up.
RWY 07R-25L: H11095X200 (ASPH-CONC-GRVD) S-175, D-225, 2D-400, 2D/2D2-900 PCN 75 R/A/W/T HIRL CL
RWY 07R: MALSR. PAPI(P4L)—GA 3.0° TCH 57'. RVR-TMR Pole. Rgt tfc.
RWY 25L: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 70'. RVR-TMR Railroad. 0.3% up.
RWY 06R-24L: H10885X150 (CONC-GRVD) S-175, D-225, 2D-400, 2D/2D2-900 PCN 70 R/A/W/T HIRL CL
RWY 06R: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 69'. RVR-TMR Thld dspcd 537'. Pole.
RWY 24L: MALSR. PAPI(P4R)—GA 3.0° TCH 79'. RVR-TMR Thld dspcd 801'. Rgt tfc.
RWY 06L-24R: H8926X150 (ASPH-CONC-GRVD) S-175, D-225, 2D-400, 2D/2D2-900 PCN 70 R/A/W/T HIRL CL
RWY 06L: MALSR. PAPI(P4L)—GA 3.0° TCH 77'. RVR-TMR Pole.
RWY 24R: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TMR Sign. Rgt tfc.

N33°56.55' W118°24.48'

LOS ANGELES
 COPTER
 H-4I, L-3E, 4G, 7B, A
 IAP, AD



RUNWAY DECLARED DISTANCE INFORMATION

RWY 06L:TORA-8926 TODA-8926 ASDA-8566 LDA-8566
RWY 06R:TORA-10285 TODA-10285 ASDA-10285 LDA-9748
RWY 07L:TORA-12091 TODA-12091 ASDA-12091 LDA-11259
RWY 07R:TORA-11095 TODA-11095 ASDA-11095 LDA-11095
RWY 24L:TORA-10285 TODA-10285 ASDA-10285 LDA-9483
RWY 24R:TORA-8926 TODA-8926 ASDA-8926 LDA-8926
RWY 25L:TORA-11095 TODA-11095 ASDA-11095 LDA-11095
RWY 25R:TORA-12091 TODA-12091 ASDA-12091 LDA-11134

SERVICE: S4 FUEL JET A OX 1, 3 LGT Rwy 24R ALSF2 operates as SSALR until weather goes below VFR. Rwy 25L ALSF2 operates as SSALR till weather goes below VFR. **MILITARY— FUEL A, A+ (C310-258-9884) FLUID LHOX**

NOISE: Noise sensitive arpt, on westerly tkfs no turns before crossing shoreline, over-ocean apchs utilized 0800-1430Z.

NOTE: See Special Notices—Noise Abatement Procedures.

AIRPORT REMARKS: Attended continuously. Rwy 07R-25L preferred emerg rwy. Numerous birds on and in/ov airport. Pilots should use ctn for poss laser act in the LAX area. Turbulence may be deflected upward from the blast fence 180' east of Rwy 25R. Major construction on arpt daily. American Eagle terminal southbound taxing acft use minimum power due to blast hazard. Any acft that comes to a stop, or has its momentum interrupted while turning and taxiing into its parking position, must stop and be towed. Acft use minimum power when taxiing vicinity terminals due blast hazard. Sbnrd turn not avbl from west remote gate 408 and west remote gate 409. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Practice instrument approaches and touch and go landings are prohibited. Acft with wingspan greater than 155 ft wb on Txl C are not auth to make left turn on Twy C10 under pwr. For acft with wingspan greater than 214' ctc LAX airside ops 424-646-5292 for arpt instructions. Twy D between Twy D7 and D8 (north of terminal one) clsd to acft with wingspan greater than 157'. Acft with wingspan gr than 198 ft obnd fm Txl D8 may not turn wbdn onto Txl D. Acft with length greater than 240' are prohibited on Taxilanes C7, C8 and C9 btn Taxilane C and Twy B. West remote gates: acft use of open gates as taxi path is prohibited (gates 406, 407, 408, 409). SIMUL ACFT OPS prohibited on TWYS L and H9 BTWN RWYS 07L-25R and Rwy 07R-25L. Simultaneous acft ops prohibited on Twy H2 and Twy G between Rwy 07L-25R and Rwy 07R-25L. Rwy status lgts in opr. Flight Notification Service (ADCUS) available. NOTE: See Special Notices—Noise Abatement Procedures.

AIRPORT MANAGER: 424-646-8251

WEATHER DATA SOURCES: ASOS (310) 568-1486 WSP

COMMUNICATIONS: D-ATIS ARR 133.8 D-ATIS DEP 135.65 310-646-2297 UNICOM 122.95

Ⓡ **SOCAL APP CON** 128.5 (045°-089°), 124.9 (090°-224°), 124.5 (225°-044°) 124.3 (App from west)

TOWER 133.9 (N. complex), 120.95 (S. complex) 119.8

GND CON 121.75 (S. complex) 121.65 (N. complex) 121.4 (west) **CLNC DEL** 120.35

Ⓡ **SOCAL DEP CON** 125.2 (225°-044°) 124.3 (Dep to west)

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 113.9

RADIO AIDS TO NAVIGATION: NOTAM FILE LAX.

(H) VORTACW 113.6 LAX Chan 83 N33°55.99' W118°25.92' 050° 1.3 NM to fld. 185/15E.

VOR portion unusable:

270°-277° byd 25 NM blo 8,000'

277°-300° byd 10 NM blo 8,000'

277°-300° byd 28 NM blo 12,000'

175°-205° byd 10 NM blo 3,000'

ILS/DME 108.5 I-UWU Chan 22 Rwy 06L. Class IE. Uses I-OSS Rwy 24R DME. Autopilot cpd apchs na blw 436' MSL.

ILS/DME 111.7 I-GPE Chan 54 Rwy 06R. Class IE. Rwy 24L HQB DME used.

ILS/DME 111.1 I-IAS Chan 48 Rwy 07L. Class ID. DME also serves Rwy 25R. DME unusable byd 25° left of course. Autopilot cpd apch na blw 925' MSL.

ILS/DME 109.9 I-MKZ Chan 36 Rwy 07R. Class IT. DME also serves LAX ILS Rwy 25L

ILS/DME 111.7 I-HQB Chan 54 Rwy 24L. Class IE. DME also serves Rwy 06R.

ILS/DME 108.5 I-OSS Chan 22 Rwy 24R. Class IIIE. DME also used by I-UWU Rwy 06L.

ILS/DME 109.9 I-LAX Chan 36 Rwy 25L. Class IIIE. DME also serves MKZ ILS Rwy 7R

ILS/DME 111.1 I-CFN Chan 48 Rwy 25R. Class IE. DME also serves Rwy 07L.

WHITEMAN (WHP)(KWHP) 1 E UTC-8(-7DT) N34°15.56' W118°24.81'

1003 B NOTAM FILE WHP

RWY 12-30: H4120X75 (ASPH) S-12.5 MIRL 1.0% up NW

RWY 12: REIL. PAPI(P2R)—GA 3.8° TCH 54'. Thld dspcd 729'.

P-line.

RWY 30: REIL. PAPI(P2L)—GA 3.8° TCH 26'. Thld dspcd 478'.

P-line. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 12: TORA-3442 TODA-4120 ASDA-3910 LDA-3181

RWY 30: TORA-3191 TODA-4120 ASDA-3940 LDA-3462

SERVICE: S4 FUEL 100LL, JET A OX 1, 3 LGT When twr clsd, arpt lgts opr continuously. Rwy 12 PAPI does not prvd obstn clnc byd 5 NM from thld.

AIRPORT REMARKS: Attended continuously. Birds on and invof arpt.

Helicopter ops 2500' MSL (1500' AGL) and below. Arpt CLOSED to helicopter training/pattern opr 0400-1600Z†. Dirt infield areas.

Helicopters advised to use care to prevent blasting dirt and debris onto movement areas.

AIRPORT MANAGER: (818) 896-5271

WEATHER DATA SOURCES: AWOS-3PT 132.1 (818) 899-9820.

COMMUNICATIONS: CTAF 135.0 ATIS 132.1 818-899-9820

UNICOM 122.95

® **SOCAL APP/DEP CON** 120.4 (VNY 280°-BUR 050°) North, 134.2 (VNY 160°-VNY 280°) West

TOWER 135.0 (1600-0400Z†) **GND CON** 125.0

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd ctc SoCal Apch at 800-448-3724.

AIRSPACE: CLASS D svc 1600-0400Z†; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE VNY.

VAN NUYS (L) VOR/DME 113.1 VNY Chan 78 N34°13.41' W118°29.50' 046° 4.4 NM to fld. 812/15E.

VOR/DME unusable:

010°-030° byd 20 NM blo 6,700'

030°-050° byd 25 NM blo 8,600'

330°-350° byd 25 NM blo 5,500'

350°-010° byd 15 NM blo 6,100'

DME unusable:

094°-096° byd 35 NM blo 5,000'

COMM/NAV/WEATHER REMARKS: Whiteman arpt altimeter setting not avbl.

LOS ANGELES

COPTER

L-3E, 4G, 7B, A

IAP, AD

