

NE-4, 15 JUL 2021 to 12 AUG 2021

ASOS 119.925  
CLNC DEL  
121.8 257.65  
132.075 269.075 (When Tower Closed)  
GNID CON  
121.8 257.65  
MARTINSBURG TOWER ★  
124.3 (CTAF) 233.7  
POTOMAC DEP CON  
126.825 239.025


▼ DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, expect RADAR vectors to POOCH, then on track 240° to SCRAM, thence . . . .

. . . . as depicted. Maintain 3000, expect clearance to filed altitude within ten (10) minutes after departure.

GLANC TRANSITION (SCRAM6.GLANC):

TOP ALTITUDE:  
3000



TAKEOFF MINIMUMS

Rwy 8: Standard.  
Rwy 26: Standard with a minimum climb of 225' per NM to 2100.

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: Turbo-jets only.

NOTE: Takeoff Rwy 8, if issued an ATC heading that requires a westbound turn, climb heading 081° to 1200 prior to turning for obstacle avoidance.

NOTE: Takeoff Rwy 26, if issued an ATC heading that requires a right turn, climb heading 261° to 2400 prior to turning for obstacle avoidance.

POOCH  
3000



NOTE: Chart not to scale.

NE-4, 15 JUL 2021 to 12 AUG 2021