ILS or LOC RWY 12

MIAMI-OPA LOCKA EXEC (OPF)

LOC/DME I-OLX	APP CRS	Rwy Idg	6000
111.55	128°	TDZE	8
Chan 52 (Y)		Apt Elev	8

T A Inop table does not apply to S-ILS 12. Helicopter visibility reduction below ¾ SM NA. VDP NA with Miami Intl altimeter setting. When local altimeter setting not received, use Miami Intl altimeter setting and increaseall DA/MDA 20 feet. For inop MALSR, increase S-LOC 12 Cats A and B visibility to 1 mile and Cats C and D visibility to 1⅜ miles.

MALSR (A5)

MISSED APPROACH: Climb to 800 then climbing left turn to 2000 on heading 090° and DHP VORTAC R-069 to JANUS INT/DHP 42.5 DME and hold.

ATIS	MIAMI APP CON	OPA LOCKA TOWER ★	GND CON	CLNC DEL
125.9	128.6 306.975	134.675 (CTAF) L	120.025	119.2

RADAR REQUIRED

MISSED APCH FIX

JANUS DHP 42.5

113.2 ZFP R-245 Chan 79

113.9 DHP R-069 Chan 86

116.7 ZBV R-326 Chan 114

069° 249°

(IF) JARNO INT I-OLX 11.2 RADAR

308°

1700

128° (4.9)

LOCALIZER 111.55 I-OLX Chan 52 (Y)

ZIKNA INT I-OLX 6.3 RADAR

1049 1049 1049 1049

312 210 156 133 180 213 328

R-341 R-358 R-069

MSA DHP 25 NM

2100

090° 270°

2900

1049 ±

DOLPHIN 113.9 DHP Chan 86

ELEV 8 D TDZE 8

128° 5.2 NM from FAF

A5 A4 27R 9L 8002 X 150 x 12 A5 6800 X 150 TWR 206 9R 4309 X 100 27L 30

MIRL Rwy 9R-27L

HIRL Rwys 9L-27R and 12-30 L

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

JARNO INT I-OLX 11.2 RADAR

ZIKNA INT I-OLX 6.3 RADAR

1700 128° 1700

GS 3.00° TCH 53

*I-OLX 2.6

I-OLX 1.2

4.9 NM 3.7 NM 1.5 NM

800 2000 hdg 090° DHP R-069 JANUS

*LOC only.

CATEGORY	A	B	C	D
S-ILS 12	208-¾ 200 (200-¾)			
S-LOC 12	520-¾ 512 (600-¾)		520-1 512 (600-1)	
CIRCLING	540-1 532 (600-1)		540-1½ 532 (600-1½)	560-2 552 (600-2)

SE-3, 15 JUL 2021 to 12 AUG 2021

SE-3, 15 JUL 2021 to 12 AUG 2021