

# DARWIN EIGHT DEPARTURE

AL-263 (FAA)

ST PAUL DOWNTOWN HOLMAN FLD (STP)

ST. PAUL, MINNESOTA

ATIS  
118.35  
CINC DEL  
121.675  
ST. PAUL TOWER\*  
119.1 257.8  
MINNEAPOLIS DEP CON  
121.2 335.65



ST. CLOUD  
112.1 STC  
Chan 58



R-172

DARWIN  
109.0 DWN  
Chan 27  
N45°05.25'-W94°27.23'

10000  
\*3800  
271°  
(167)

R-088

ABERDEEN  
113.0 ABR  
Chan 77  
N45°25.04'-W98°22.12'

L-14, H-2


R-095

(20)

INJUNE  
N45°01.01'  
W93°59.54'

MINNEAPOLIS  
115.3 MSP  
Chan 100  
N44°53.79'-W93°14.19'

FLYING CLOUD  
117.7 FCM  
Chan 124



### TAKEOFF MINIMUMS

- Rwy 9: Standard with minimum climb of 340' per NM to 1300.
- Rwy 13: Standard with minimum climb of 235' per NM to 1500.
- Rwy 14: Standard.
- Rwy 27: 600-2 or standard with minimum climb of 442' per NM to 1500.
- Rwy 31: NA-obstacles.
- Rwy 32: Standard with minimum climb of 340' per NM to 3000.

NOTE: RADAR required.  
NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

# DARWIN EIGHT DEPARTURE

ST. PAUL, MINNESOTA  
ST PAUL DOWNTOWN HOLMAN FLD (STP)