VOR RWY 21R
TRI-CITIES (PSC)

VOR/DME PSC	APP CRS	Rwy Idg	7110
109.8	217°	TDZE	404
Chan 35		Apt Elev	410

DME required.

VDP NA when using Hermiston altimeter setting. When local altimeter setting not received, use Hermiston altimeter setting and increase all MDA 100 feet and increase S-21R Cat C/D visibility ⅜ SM and Circling Cat C/D visibility ¼ SM. For inop ALS when using Hermiston altimeter setting, increase Cat C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climbing left turn to 3200 on heading 080° and PSC VOR/DME R-092 PSC VOR/DME to CITYS INT/PSC 14 DME and hold.

ATIS	CHINOOK APP CON★	TRI-CITIES TOWER★	GND CON	CLNC DEL	UNICOM
125.65	128.75 377.2	135.3 (CTAF) L 323.6	121.8	120.0	122.95







CATEGORY	A	B	C	D
S-21R	940/24	536 (600-½)	940/55	536 (600-1)
C CIRCLING	940-1	530 (600-1)	1040-1¾ 630 (700-1¾)	1100-2¼ 690 (700-2¼)

REIL Rwys 3L and 12
MIRL Rwy 12-30 L
HIRL Rwy 3L-21R L

NW-1, 15 JUL 2021 to 12 AUG 2021
NW-1, 15 JUL 2021 to 12 AUG 2021