VOR or TACAN RWY 17

WALLOPS FLIGHT FACILITY (WAL)

VORTAC SWL	APP CRS	Rwy Idg	4808
112.4	190°	TDZE	39
Chan 71		Apt Elev	40

When local altimeter setting not received, use Salisbury altimeter setting and increase all MDA 60 feet and S-17 Cats C/D and Circling Cat C visibility ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct SWL VORTAC and hold. (TACAN aircraft climb to 600 then climbing right turn to 2000 on heading 300° and SWL VORTAC R-219 to WAFIT/SWL 5 DME and hold SW, LT 039° inbound.)

ASOS	PATUXENT APP CON ★	WALLOPS TOWER ★	GND CON	CLNC DEL
119.175	127.95 314.0	126.5 (CTAF) L 306.975 (CTAF) L	127.875 269.325	121.7





REIL all Rwys
HIRL Rwys 4-22, 10-28 and 17-35

FAF to MAP 6.6 NM					
Knots	60	90	120	150	180
Min:Sec	6:36	4:24	3:18	2:38	2:12



CATEGORY	A	B	C	D
S-17	540-1	501 (500-1)	540-1⅜	501 (500-1⅜)
C CIRCLING	600-1	560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)

NE-3, 15 JUL 2021 to 12 AUG 2021
NE-3, 15 JUL 2021 to 12 AUG 2021