

KEESLER AFB (BIX)(KBIX) AF (AFRC) 0 W UTC-6(-5DT) N30°24.63' W88°55.47'

NEW ORLEANS

33 B TPA—See Remarks NOTAM FILE BIX Not insp.

H-7E, 8F, L-21C, 22G, GOMC

RWY 04-22: H7630X150 (PEM) PCN 32 F/B/W/T HIRL

DIAP, AD

RWY 04: REIL. PAPI(P4L)—GA 3.0° TCH 48'. Thld dsplcd 1600'. Trees-I.

RWY 22: ALSF1. PAPI(P4L)—GA 3.0° TCH 55'. Thld dsplcd 1000'. Trees-I. Rgt tfc.

SERVICE: S4 **FUEL** 115, JET A+++, B+ **OX2** **LGT** NSTD rwy edge and twy lgts; svrl lgts gtr than 200 ft dist apart on rwy, svrl missing twy exit lgts. SFL OTS UFN. Rwy 22 lgts: ALSF-1 NSTD len 2000'. **MILITARY—** **JASU** 1(MA-1A)

3(A/M32A-86A) **FUEL** A++ **FLUID** SP PRESAIR LPOX LOX OIL O-148-156 **TRAN ALERT** Tran maint opr 1400-2300Z‡

Mon-Fri, OT with prior coord; ctc AMOPS DSN 597-2120.

MILITARY REMARKS: Opr 1400-0500Z‡ Mon-Fri, clsd hol; weekend hrs: Unit Trng Assembly (UTA) weekends normally first weekend of month, Sat 1700-2300Z‡, Sun 1630-0500Z‡. All non-UTA weekends afld will be clsd but avbl to open with prior coord; ctc AMOPS DSN 597-2120. PPR All acft, PPR all acft after tran maint opr ctc Afld mgmt OPS at DSN 597-2120. See FLIP AP/1 Supplementary Arpt Remark. **RSTD** Aircrews ctc GND prior to acft engine start. Pilots will avoid flying over the USAF Medical Center located on the Back Bay 1 NM E of rwy, and the VA Hospital on the Back Bay 1 NM W of rwy. Twy E 50' width. Acft rinse facility (Bird Bath) Twy C avbl to C-130 and larger acft. All C-130 or larger must face N on Twy B for maintenance runs or engine run-ups. **CAUTION** GS ant 250' W of cntrln and 1050' from AER 22. BASH Phase II in eff 1 Jun-30 Sep; exp heavier bird act SR-SS. Marina trees hinder wind, low wind speed on Rwy 22 when wind dir from 280°-340°. Dur augmentation/backup; ltd wx obsn to E and vis mkr byd 1 sm avbl in the W to N sector, night flood lgt hinder cloud and vis obsn, and ceil fre 100' -200' lower than obsn on Rwy 22 acft from Nov-Mar. Ctc twr with req to back taxi. Rwy edge lgts past thresholds greater than 10' from full strength pavement. Spot 24/25 (Twy B and Twy F) light—alls used when C-17 park during hrs of darkness and inclement wx. First 100 ft conc spherical bollards lctd 440 ft sw of cntrl. Rwy hazard men or equipment opr randomly to include within 100' of rwy daily. Large frame and heavy acft will make 180° turns on concrete portion of rwy. Night vision devices training Tue and Thu 0200-0400Z‡. Rwy 04-22 eff len 5030 ft for TGL ops. **TFC PAT** TPA—Overhead 1500(1467), Conventional 1000(967), Helicopter 500(467). Rwy 04-22 eff len 5030' for tgl ops. **MISC** Rwy 04 displ thld dimensions and sfc—1st 200' is concrete, next 800' mid 75' is concrete outer with 37.5' non-wt brg asphalt edge ea side, and remaining 598' X 150' is concrete. Rwy 22 displ thld dimensions and sfc—1st 200 X 150 is concrete, next 800 X 75 is concrete with 37.5' non-wt brg asphalt edge ea side. VIP acft ctc PTD 372.2 15 minutes prior to ldg with firm chock time. During opr hours, LIFE GUARD/MEDEVAC/SAR/MSN essential acft ctc Afld Management OPS DSN 597-2120, C228-377-2120 1 hour prior to arr for proper coordination, during non-opr hours, ctc Command Post DSN 597-4330, C228-377-4330 1 hour prior to req airfield be opened. Hangar space not avbl for severe weather. Rwy 04 avbl tkf 6632' from key-hole. Rwy 22 avbl tkf 6034' from key-hole. See US Terminal Low Arpt Sketch for NSTD Rwy 04-22 configuration. COMSEC materials are not avbl. Assault Zone marker on rwy. Rwy Surface Condition/Rwy Condition Reading not reported during published afld clsd times. **403 WG AFRC** C130/WC130 acft opr weekdays.

AIRPORT MANAGER: 228-377-2123

COMMUNICATIONS: ATIS 281.55 (Opr 1400-0500Z‡ Mon-Fri, 1700-2300Z‡ Sat and Sun, clsd hol, Unit Trng Assemblies 1700-2300Z‡ Sun) **PTD** 372.2

® **GULFPORT APP/DEP CON** 124.6 354.1 (130°-309°) 127.5 254.25 (310°-129°) (1200-0500Z‡)

® **HOUSTON CENTER APP/DEP CON** 132.6 316.075 (0500-1200Z‡)

TOWER 120.75 269.075 (Opr 1400-0500Z‡ Mon-Fri, 1700-2300Z‡ Sat and Sun, clsd hol, Unit Trng Assemblies 1700-2300Z‡ Sun)

GND CON 121.8 275.8 **CLNC DEL** 121.8 275.8

403 WG AFRC COMD 252.8 (Call ACCOUNTANT) **PMSV METRO** 267.4 Full svc avbl 24 hrs from 0400Z‡ Mon thru 0500Z‡ Sat (2200 Local Sun thru 2300L Fri), clsd weekends and hol exc for unit trng assembly (UTA) weekends; UTA opr hrs 1600-2300Z‡ Sat and 1300Z‡ Sun-0400Z‡ Mon. Remote briefing svc avbl from 26 OWS Barksdale AFB, LA, DSN 331-2651, C318-529-2651. Automatic FMQ-19 in use 24/7. Augmented/backed up FMQ-19 in use when required during opr hrs and for resource protection. ASOS obsn avbl at DSN 597-0438 or C228-377-0438.

AIRSPACE: CLASS D svc 1400-0500Z‡ Mon-Fri, 1700-2300Z‡ Sat and Sun, clsd hol, uta 1900-0500Z‡ Sun; other times CLASS E.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE BIX.

(T) TACAN Chan 55 BIX (111.8) N30°24.43' W88°55.78' at fld. 20/2W.

mnt dur publ opr hr only
No NOTAM MP: 1200-1400Z± Wed (1000/2+1)

TACAN AZIMUTH unusable:

110°-120° byd 15 NM
148°-158° byd 15 NM

DME unusable:

110°-120° byd 15 NM
148°-158° byd 15 NM

GULFPORT (L) VORTAC 109.0 GPT Chan 27 N30°24.41' W89°04.61' 086° 7.9 NM to fld. 25/2E. NOTAM FILE GPT.

TACAN AZIMUTH unusable:

195°-217°
266°-275° byd 12 NM

VOR unusable:

035°-086° blo 5,000'
293°-303°

ILS 109.7 I-BIX Rwy 22. Class IB. Mnt 1400-0500Z±. No NOTAM MP: 1200-1400Z± Tue and Thu (1,000/2+1). ILS critical area not protected. Radar: see terminal flip for radar minima.

KEWANEE N32°22.06' W88°27.43' NOTAM FILE GWO.

MEMPHIS

(L) DME 113.8 EWA Chan 85 131° 22.4 NM to Butler-Choctaw Co. 342/0E.

L-18H

DME unusable:

Byd 30 NM blo 3,000'

KEY FLD (See MERIDIAN on page 150)

KOSCIUSKO-ATTALA CO (OSX)(KOSX) 3 NE UTC-6(-5DT) N33°05.42' W89°32.52'

MEMPHIS

494 B NOTAM FILE GWO

H-6J, L-18G

RWY 14-32: H5009X75 (ASPH) S-18 MIRL 0.5% up NW

IAP

RWY 14: PAPI(P2L)—GA 3.5° TCH 38'. Trees.

RWY 32: PAPI(P2L)—GA 3.5° TCH 49'. Trees.

SERVICE: FUEL 100LL, JET A LGT ACTVT MIRL Rwy 14-32—CTAF.

PAPI Rwy 14 and Rwy 32 opr consly.

AIRPORT REMARKS: Unattended. Wildlife on and invof arpt. RC model airplane flying off rwy end. Courtesy car avbl.

AIRPORT MANAGER: 662-289-1226

COMMUNICATIONS: CTAF 122.9

Ⓡ MEMPHIS CENTER APP/DEP CON 132.75

CLEARANCE DELIVERY PHONE: For CD ctc Memphis ARTCC at 901-368-8453/8449.

RADIO AIDS TO NAVIGATION: NOTAM FILE GWO.

SIDON (H) VORTAC 114.7 SQS Chan 94 N33°27.83'

W90°16.64' 118° 43.2 NM to fld. 127/3E.

