

APP CRS	Rwy Idg	10591
078°	TDZE	1118
	Apt Elev	1135


RNAV (RNP) Z RWY 8

PHOENIX SKY HARBOR INTL (PHX)



▼ GPS required. Visibility reduction by helicopters NA.
 For uncompensated Baro-VNAV systems, procedure NA below 1°C (34°F) or above 46°C (116°F).
 For inoperative MALSF, increase RNP 0.13 all Cats visibility to 1¼, and RNP 0.30 all Cats visibility to 1¾.

MALSF MISSED APPROACH: Climb to 5000 via track 078° to YOKXO and via track 114° to IWA VORTAC and hold.

D-ATIS	PHOENIX APP CON	PHOENIX TOWER	GND CON	CLNC DEL	CPDLC
127.575	128.65 353.9	118.7 278.8 (Rwy 8-26) 120.9 254.3 (Rwy 7L-25R, 7R-25L)	119.75 269.2 (N) 132.55 269.2 (S)	118.1 269.2	



ELEV	1135	D	TDZE	1118
------	------	----------	------	------



CATEGORY	A	B	C	D
RNP 0.13 DA		1478-1	360 (400-1)	
RNP 0.30 DA		1603-1½	485 (500-1½)	

AUTHORIZATION REQUIRED

SW-4, 09 SEP 2021 to 07 OCT 2021

SW-4, 09 SEP 2021 to 07 OCT 2021