ILS or LOC RWY 17

CORVALLIS MUNI (CVO)

LOC I-CVO	APP CRS	Rwy Idg	5900
111.9	172°	TDZE	248
		Apt Elev	250

ADF required for procedure entry. ADF required for LOC only.

Circling Rwy 28 NA at night. When local altimeter setting not received, procedure NA. For inop ALS, increase S-LOC 17 Cat C/D visibility to 2 SM.

MALSR

MISSED APPROACH: Climb to 900 then climbing left turn to 3000 on heading 050° and on CVO VOR/DME R-081 to SHEDD INT/EUG 22.1 DME and hold, continue climb-in-hold to 3000.

AWOS-3PT	CASCADE APP CON ★	UNICOM
135.775	127.5 348.7	123.075 (CTAF)

ALTERNATE MISSED APCH FIX

LEWISBURG LWG 225

172° 352°

BREAF UBG 20

4300 to NDB 181° (26.1)

4100 to NDB 207° (19.6)

TURNO 266 SL

EUG 45.1

CRAAF UBG 39

4300 to NDB 144° (9.5)

352° 217° 037°

(CFFSK)

172°

2686

2096

3800 to NDB 237° (11.6)

MAGOT EUG 34.4

1757

ZIKDO CVO 8.1

IAF LEWISBURG 225 LWG

CVO 6.9

1741

1316±

MSA LWG 25 NM

148° 3900 238° 5300 4900 328°

112.9 EUG Chan 76

CORVALLIS 115.4 CVO Chan 101

4000 to NDB 350° (6.9)

4097

LOCALIZER 111.9 I-CVO

388

360° 180°

R-081

SHEDD EUG 22.1

1632

380

R-360

ELEV 250 D TDZE 248

172° 6.7 NM from FAF

3100 X 75

5900 X 150

10 28

35

REIL Rwy 35 L

MIRL Rwys 10-28 and 17-35 L

FAF to MAP 6.7 NM

Knots	60	90	120	150	180
Min:Sec	6:42	4:28	3:21	2:41	2:14

900	3000 hdg 050°	CVO R-081	SHEDD

*LOC only.

LWG NDB CVO 6.9

Remain within 10 NM

352° 3300

ZIKDO CVO 8.1

172° 2800

2800

2500*

*CVO 2.5

CVO 0.3

GS 3.00° TCH 45

2.2 NM 4.5 NM 1.2 NM

CATEGORY	A	B	C	D
S-ILS 17	448-½ 200 (200-½)			
S-LOC 17	1000-½ 752 (800-½)	1000-¾ 752 (800-¾)	1000-1¾ 752 (800-1¾)	
C CIRCLING	1000-1 750 (800-1)	1000-1¼ 750 (800-1¼)	1000-2¼ 750 (800-2¼)	1080-2¾ 830 (900-2¾)

NW-1, 09 SEP 2021 to 07 OCT 2021
NW-1, 09 SEP 2021 to 07 OCT 2021