ILS or LOC RWY 32

WINCHESTER RGNL (OKV)

LOC/DME I-TZX	APP CRS	Rwy Idg	5498
109.55	324°	TDZE	715
Chan 32 (Y)		Apt Elev	726

Rwy 32 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Martinsburg altimeter setting and increase all DA 63 feet and all MDA 80 feet and Circling Cat C visibility ¼ mile. For inoperative MALSR, increase S-LOC 32 Cat C visibility to 1 mile. For inoperative MALSR when using Martinsburg altimeter setting, increase S-ILS 32 All Cats visibility ½ mile. VDP NA when using Martinsburg altimeter setting.

NA

MALSR

MISSED APPROACH: Climb to 1400 then climbing right turn to 3700 via heading 160° and I-TZX SE course to CLADD INT/I-TZX 12.6 DME and hold.

AWOS-3	POTOMAC APP CON	CLNC DEL	UNICOM
124.85	120.45 306.925	126.15	122.7 (CTAF)







CATEGORY	A	B	C	D
S-ILS 32	915-½ 200 (200-½)			
S-LOC 32	1040-½ 325 (400-½)			1040-¾ 325 (400-¾)
C CIRCLING	1180-1 454 (500-1)	1220-1 494 (500-1)	1380-1¾ 654 (700-1¾)	1480-2½ 754 (800-2½)

REIL Rwy 14 L
HIRL Rwy 14-32 L

FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

NE-3, 09 SEP 2021 to 07 OCT 2021
NE-3, 09 SEP 2021 to 07 OCT 2021