

RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (REEVES FIELD)(KNLC), Leemore, CA Amdt 7

17JUN21 (21168) (USN)

ELEV 228

RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ^{1,4}	32L ^{2,6}	3.0°/40/743	ABCDE	327/12	100	(100-¼)
	14L	3.0°/54/983	ABCDE	319/24	100	(100-½)
	32R ⁵	3.0°/46/870	ABCDE	321/24	100	(100-½)
	14R ⁵	3.0°/52/977	ABCDE	328/24	100	(100-½)
ASR ⁴	32L ^{3,7}		AB	580/24	353	(400-½)
			CDE	580/30	353	(400-⅝)
	14L		ABCDE	560/55	341	(400-1)
	14R ⁵		AB	680/55	452	(500-1)
			CDE	680-1¾	452	(500-1¾)
	32R ⁵		AB	760/55	539	(600-1)
CDE			760-1½	539	(600-1½)	
CIR ⁸	14L, 14R, 32L		AB	680-1	452	(500-1)
			C	700-1½	472	(500-1½)
			DE	780-2	552	(600-2)
	32R		AB	760-1	532	(600-1)
			C	760-1½	532	(600-1½)
			DE	780-2	552	(600-2)

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.

²When ALS inop, increase CAT ABCDE RVR to 24 and vis to ½ mile.

³When ALS inop, increase CAT ABCDE RVR to 55 and vis to 1 mile.

⁴Simultaneous approaches authorized.

⁵Pattern at 2800 ft.

⁶Caution: WCH group 4: 15 ft less than required 20 ft.

⁷Step Down Fix at 3 NM from thld, 1100 min.

⁸Circling authorized only from ASR.

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021

RADAR INSTRUMENT APPROACH MINIMUMS