

**MACDILL AFB** (MCF)(KMCF) AF (A) 4 S UTC-5(-4DT) N27°50.96' W82°31.27'

MIAMI

14 B LRA NOTAM FILE MCF Not insp.

H-8H, L-21D, 24F

**RWY 05-23:** H11421X151 (ASPH-GRVD) PCN 71 R/B/W/T HIRL

DIAP, AD

**RWY 05:** ALSF1. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T

**RWY 23:** ALSF1. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T

**ARRESTING GEAR/SYSTEM**

**RWY 05** HOOK BAK-12B(B) (1338 FT); UNAVBL DURG WKND & FED HOL; AVBL MON-FRI 1300Z-2030Z++; 45 MIN PPR TO CONNECT CABLE.

HOOK BAK-12B(B) (1397 FT); UNAVBL DURG WKND & FED HOL; AVBL MON-FRI 1300Z-2030Z++; 45 MIN PPR TO CONNECT CABLE. **RWY 23**

**SERVICE:** **FUEL** 115, JET A, A++ **OX 2** **MILITARY**—LGT HIRL Rwy 05-23 opr when twr opn. Rwy 05-23 PAPI set for hgt group 3. **A-GEAR** S BAK-12B O/S UFN. **JASU** (A/M32A-86) (AM32-95) (M32A-60) **FUEL** A++. Air Card rqrd for avn fuel or U.S. cash; cash fuel PPR—fuels DSN 968-2074. **FLUID** LPOX LOX **TRAN ALERT** Opr 1100-0300Z†. Lavatory svc only, PPR. Ltd tran prk for tactical acft; exp svc delay for tactical acft. Unable to svc acft with ordnance. Tran Alert is contract maint. Tran acft must land by 0230Z† exc VIP. All frt type/trainer acft must land by 0200Z†. No multiple IFR/VFR apch for tran acft after 0230Z†. Tran Alert can support minimal tran acft for lcl or out and back tran flts with prior apvl. All series B-747 and A-380 must arrive with a tow bar.

**MILITARY REMARKS:** Attended continuously. See FLIP AP/1 Fit Haz (Florida—R2901) and Supplementary Arpt Rmk and afterburner proc. Rwy 05-23 mkd 150 ft wide with 50 ft wt brg shoulders each side. First 1000 ft conc mid 9420 ft asph. **RSTD** Avoid ovft of the St. Petersburg land mass by at least 1.5 NM. PPR—Base Ops DSN 968-2929/2350, C813-828-2350/2929, for PPR nr, for svc and other rstd. PPR issued up to 7 days prior to arr. All acft must land by PPR approved time or call with deviations or PPR is invalid; exc for VIP. Aflid mgmt must rqr FPL for acft prior to dep. All DV acft and tntst acft ctc MacDill Cmd Post 311.0 or DSN 968-4361/4362 (C813-828-4361) 3 hr prior to arr and 30 min prior to arr with DV codes, customs info and Space-A pax info. All aircrew dep civ arpt or guard/reserve base call Comd Post 1 hr prior to takeoff with pax/cargo/eta info. PPR number good for req day only. S ramp (B ramp), electrical box 116' and fence 138' from twy cntrln. Acft opr rstd dur Bird Watch Cond Moderate (tkf or ldg permission only when departure and arr rte avoid identification bird act. No lcl IFR/VFR tfc pat act) and Severe (tkf and ldg prohibited without OG/CC apvl), etc ATIS, Twr, Comd Post, or AMOPS for current Bird Watch Cond. All acft dep MacDill AFB, with exc to no DOD affiliated acft, must leave copy of FPL with Aflid Mgmt. Bravo Ramp parking spot B4 clsd for all acft. Cargo/hvy acft lndg on BAK-12 cables na. **CAUTION** Bird haz; exp hvy bird act fm Nov 1-Feb 28 durg Phase II BASH period; 24 hr bird watch alert in effect. Numerous voids/sinkholes on aflid; remain on twy cntrln. See FLIP AP/1 Supplementary Arpt Remarks for bird haz info. On inst apch to Rwy 23, use caution dur ovft of Peter O. Knight Arpt due to lgt acft tfc blw apch leg 4 NM NE. Commercial acft cross apch to MacDill AFB enroute to Tampa Intl Arpt at and abv 2100 ft. On inst apch to Rwy 05 use caution dur ovft of Albert Whitted Arpt due to lgt tfc blw apch leg 6 NM SW. Maint rwy and twy cntrline when exiting rwy. Acft making 180° turns on rwy use hammerheads last 1000 ft at each end. Use ctn durg taxiing ops at night on spots A1-A4 due to removed apn lgtg. Taxilane H, fence 107' from twy cntrln, all acft larger than KC-135 need wing walkers and tran alert follow me vehicle. S ramp (Bravo ramp) electrical box 116' from twy cntrln and fence 138' from twy cntrln, all acft larger than KC-135 need wing walkers and tran alert follow me vehicle. DV-4 spot is for C12, C21 acft tight turn radius. Unctl VFR tfc in vcnty of KMCF blw 1200'. NSTD ovrn mrk MacDill AFB on Rwy 05-23 ends. NSTD mrks north/south ramps, wing-tip obst lines for trng. NSTD acft turning RAD on tran spots 16-25, follow tran alert vehicle. Birdbath only used for P-3, C-130, E-3A, KC-135 & B-737 acft no frt or copter unless apvd by afm. **TFC PAT** Rectangular 1100 ft; ovhd 1600 ft. Drg VFR cond tkof and TGL mntn 1100 ft til DER. **CSTMS/AG/IMG** CSTMS/AG/IMG See FLIP AP/1. **MISC** MacDill crash fire response (CFR) is an acft rescue and firefighting (ARFF) CAT 4 with 7,800 gal capability steady. ARFF cond for MacDill AFB is optimum level of svc (OLS) for CAT 1-4, and reduced level of svc (RLS) for CAT 5-6. ATG/Wx will not incltd/relay wind correction into fcst/phraseology, therefore, aircrews will incorporate a +/- . Wx flt ops 24 hrs. Excld hol or dur severe wx. Wx flt DSN 968-4405/2854/2035, C813-828-4405/2854/2035. During aflid closures ctc 26 OWS, DSN 331-2651, C318-529-2651. When possible, provide 2 hr adv ntc for all rqrd briefings. When NVD ops are in effect ctc twr 10 min prior to arr or dep for aflid lgt adj—info DSN 968-2120/4822. NOTE: See Special Notices—Airspace delegated to MACDILL AFB.

**COMMUNICATIONS:** SFA ATIS 133.825 270.1 PTD 372.2

Ⓡ TAMPA APP CON 124.95 354.0

**TOWER** 120.175 294.7 **GND CON** 118.575 275.8

Ⓡ TAMPA DEP CON 119.9 290.3 353.575 (Rwy 05) 119.65 353.575 (Rwy 23)

**6 AMW COMD POST** (LIGHTNING OPS) 311.0 323.8 **PMSV METRO** 225.05

**AG** See Global HF Sys listing in Flight Information Handbook.

**AIRSPACE:** CLASS D svc continuous.

CONTINUED ON NEXT PAGE

## CONTINUED FROM PRECEDING PAGE

**RADIO AIDS TO NAVIGATION:** NOTAM FILE MCF.

(L) **TACAN** Chan 47 MCF (111.0) N27°51.67' W82°30.81' at fld. 12/6W.

mp 0900-2300Z Fri  
**TACAN AZIMUTH** unusable:  
 230°-240° byd 30.0 NM  
 240°-245° byd 30 NM  
 246°-341° byd 35 NM  
 342°-345°  
 346°-011° byd 35 NM

**DME** unusable:  
 230°-240° byd 30 NM  
 241°-284° byd 35 NM  
 296°-345° byd 35 NM  
 342°-345° byd 32 NM  
 346°-011° byd 35 NM

**ILS** 109.5 I-MCF Rwy 05. Class IC. ILS - 05: Rwy 05 course line is offset 2.9° to se, rwy hdg is 046 deg. Rwy 23 course line is offset 2.7° to ne, rwy hdg is 226 deg. Mp 0900-1200Z Tue-Wed.

**ILS** 111.7 I-GBZ Rwy 23. Class IB. Rwy 23 course line is offset 2.7° to ne, rwy hdg is 226 deg. Mp 1200-1500Z Tue-Wed.

**COMM/NAV/WEATHER REMARKS:** MacDill surveillance radar provided by Tampa. Tsnt aircrews may ctc 9 OWS for WX BRIEF-DSN 965-0939.

**MANATEE** (See PALMETTO on page 143)

**MARATHON**

**THE FLORIDA KEYS MARATHON INTL** (MTH)(KMTH) 3 E UTC-5(-4DT) N24°43.57' W81°03.08'

**MIAMI**

5 B LRA ARFF Index-See Remarks NOTAM FILE MTH

**H-81, L-23C**

**RWY 07-25:** H5008X100 (ASPH-GRVD) S-75, D-129, 2D-191

**IAP**

PCN 94 F/A/W/T MIRL

**RWY 07:** REIL. PAPI(P4L)-GA 3.0° TCH 24'. Tree.

**RWY 25:** PAPI(P4L)-GA 3.0° TCH 24'. Tree.

**RUNWAY DECLARED DISTANCE INFORMATION**

**RWY 07:** TORA-5008 TODA-5008 ASDA-5008 LDA-5008

**RWY 25:** TORA-5008 TODA-5008 ASDA-5008 LDA-5008

**SERVICE:** S2 FUEL 100LL, JET A1+ OX 1, 2, 3, 4 LGT ACTIVATE REIL Rwy 07; PAPI Rwy 07 and Rwy 25; MIRL Rwy 07-25-CTAF.

**NOISE:** Noise sens area; use NBAA noise abatement proc; lcl ordinance rqr eng runup in dsgrd area on coml or FBO ramp fm 0400-1200Z and fines.

**AIRPORT REMARKS:** Attended 1300-2300Z. Birds on and invof arpt. Aft hr Jet-A fuel-305-481-7615. Self svc fuel H24. Class I, ARFF Index A. 48 hr PPR for unskd Part 121 ops with grt than 30 pax seats. 24 hr PPR for acft with wingspan 95 ft or grt. Rwy 07-25 has 200 ft nonstandard sepn dist fm twy to rwy cntrn-amgr or 305-743-1995. Twy A clsd to acft with wingspan 79 ft or grt when acft with wingspan of 95 ft or grt ldg or tkof Rwy 07-25. Arpt ops notification will be tmtd on CTAF. CBP user fee fac Wed-Sun 1400-2130Z. Clsd to arr Mon and Tues exc CBP apre-305-289-2029. See Special Notices-U.S. special customs requirement. Flight Notification Service (ADCUS) avbl.

**AIRPORT MANAGER:** 305-289-6302

**WEATHER DATA SOURCES:** ASOS 135.525 (305) 743-8373.

**COMMUNICATIONS:** CTAF/UNICOM 122.975

**MARATHON RCO** 122.6 (MIAMI RADIO)

**MIAMI CENTER APP/DEP CON** 133.5

**CLEARANCE DELIVERY PHONE:** For CD if una to ctc on FSS freq, ctc Miami ARTCC at 305-716-1731.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE EYW.

**KEY WEST (H) VORTAC** 113.5 EYW Chan 82 N24°35.15' W81°48.03' 077° 41.8 NM to fld. 10/1E.

VOR unusable:

025°-059° blo 3,000'  
 060°-093° byd 20 NM blo 5,000'  
 085°-095° byd 12 NM blo 1,600'  
 094°-140° byd 20 NM  
 270°-280° byd 20 NM  
 337°-352° byd 20 NM  
 190°-255°

TACAN unusable:

123°-133° byd 20 NM

**MARATHON NDB (HW)** 260 MTH N24°42.71' W81°05.72' 074° 2.5 NM to fld. 6/4W. NOTAM FILE MTH.

