

**TOP ALTITUDE:  
ASSIGNED BY ATC**

D-ATIS DEP 135.65  
CLNC DEL 120.35 327.0  
CPDLC  
GND CON (N) 121.65 327.0  
(S) 121.75 327.0  
(W) 121.4 327.0  
LOS ANGELES TOWER (N) 133.9 239.3  
(S) 120.95 379.1  
SOCAL DEP CON 124.3 363.2 (045°-224°)  
125.2 263.025 (225°-044°)

SAN MARCUS  
114.9 RZS  
Chan 96  
N34°30.57'-W119°46.26'  
L-3-4-7, H-4

VENTURA  
108.2 VTU  
Chan 19  
N34°06.90'-W119°02.97'

SANTA MONICA  
110.8 SMO  
Chan 45

SUDDO  
N34°23.03'  
W120°07.73'

DINTY  
N33°28.97'  
W122°35.04'  
H-4

**TAKEOFF MINIMUMS**

Rwys 6L/R, 7L/R, 24L/R, 25L/R: Standard.

NOTE: RADAR required.

NOTE: DINTY TRANSITION: DME required.

NOTE: Chart not scale.

**DEPARTURE ROUTE DESCRIPTION**

TAKEOFF RUNWAYS 6L/R, 7L/R: Climb on heading 071° for RADAR vectors to VTU VOR/DME, thence. . . .

TAKEOFF RUNWAYS 24L/R, 25L/R: Climb on heading 251° for RADAR vectors to VTU VOR/DME, cross SMO R-154 at or below 3000, thence. . . .

. . . .on (assigned route). All aircraft expect further clearance to filed altitude 5 minutes after departure.

LOST COMMUNICATIONS: If not in contact with Departure Control within five minutes after departure climb to FL230 or filed altitude, whichever is lower. Aircraft filing FL240 or above climb to filed altitude ten minutes after departure.

DINTY TRANSITION (VTU8.DINTY): From over VTU VOR/DME on VTU R-272 to SUDDO INT then on RZS R-233 to DINTY.

SAN MARCUS TRANSITION (VTU8.RZS): From over VTU VOR/DME on VTU R-289 and RZS R-109 to RZS VORTAC.