ILS or LOC RWY 36R

MEMPHIS INTL (MEM)

LOC/DME I-MYO	APP CRS	Rwy ldg	9000
111.35	360°	TDZE	335
Chan 50 (Y)		Apt Elev	341

T A For inoperative ALSF, increase S-ILS 36R Cat E visibility to RVR 4000 and S-LOC 36R Cat E visibility to 1½ . Simultaneous approach authorized with Rwy 36L. DME or RADAR required.

ALSF-2 (A)

MISSED APPROACH: Climb to 1000 then climbing right turn to 5000 via heading 070° and MEM VORTAC R-040 to OROCU INT/MEM VORTAC 15 DME and hold, continue climb-in-hold to 5000.

MEMPHIS APP CON	MEMPHIS TOWER		GND CON		CLNC DEL
119.1 291.6 (176°-355°)	(Rwy 9-27)	118.3 257.8	(Rwy 9-27)	121.0 379.2	125.2
125.8 338.3 (356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7 257.8	(Rwys 18C-36C, 18L-36R)	121.9 379.2	
	(Rwy 18R-36L)	128.425 257.8	(Rwy 18R-36L)	121.65 379.2	

D-ATIS 127.75

CPDLC

RADAR REQUIRED



ELEV 341 D TDZE 335



360° 5 NM from FAF

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40



CATEGORY	A	B	C	D	E
S-ILS 36R	535/18 200 (200-½)				535/24 200 (200-½)
S-LOC 36R	760/24 425 (500-½)		760/40 425 (500-¾)		760/50 425 (500-1)
C CIRCLING	940-1 599 (600-1)		940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)	1140-2¾ 799 (800-2¾)

SE-1, 02 DEC 2021 to 30 DEC 2021
SE-1, 02 DEC 2021 to 30 DEC 2021