

RADAR MINS

21196

N1

RADAR INSTRUMENT APPROACH MINIMUMS

ALBEMARLE, NC
STANLY COUNTY (VUJ)
RADAR-1 128.325 307.8 ▾

Orig, 22JUN17 (19059) (FAA)

ELEV 609

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	22L	3.0°/40/767	ABCD	784-¾	200	(200-¾)

Procedure NA when control tower closed.

BEAUFORT, SC
BEAUFORT EXECUTIVE (ARW)
RADAR-1 125.125 292.125 ▲ NA

Amdt 3A, 10MAY07 (20310) (FAA)

ELEV 10

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	25		ABC	440-1¼	430	(500-1¼)				
CIRCLING	ALL RWY		AB	500-1¼	490	(500-1¼)	C	500-1½	490	(500-1½)

Use Beaufort MCAS/Merritt Field altimeter setting.
When Beaufort Class D not in effect, procedure NA.

02 DEC 2021 to 30 DEC 2021

02 DEC 2021 to 30 DEC 2021

SE-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

21196

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BEAUFORT MCAS (MERRITT FLD) (KNBC), Beaufort, SC

Amdt 6 15JUL21 (21224) (USN)

ELEV 37

RADAR - (E) 123.7x 298.875x 317.775x 323.275x 338.35x 372.0x 379.275x **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR ¹	5 ^{2 8}	3.0°/38/780	ABCDE	137-¼	100	(100-¼)
	23 ^{2 9}	3.0°/44/837	ABCDE	116-¼	100	(100-¼)
	14 ³	3.0°/41/777	ABCDE	233-¾	200	(200-¾)
	32 ⁴	3.0°/40/764	ABCDE	308-⅞	283	(300-⅞)
PAR W/O GS ¹	23 ^{5 6}		AB	360-½	344	(400-½)
			CDE	360-⅝	344	(400-⅝)
	14 ⁶		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
	5 ⁷		AB	440-¾	403	(500-¾)
			CDE	440-1	403	(500-1)
	32 ⁶		AB	440-1	415	(500-1)
			CDE	440-1½	415	(500-1½)
			AB	360-½	344	(400-½)
			CDE	360-⅝	344	(400-⅝)
ASR ¹⁶	14		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
	5 ⁷		AB	440-¾	403	(500-¾)
			CDE	440-1	403	(500-1)
	32		AB	500-1	475	(500-1)
			CDE	500-1½	475	(500-1½)
	CIR	5, 14, 23, 32	AB	500-1	463	(500-1)
			C	580-1½	543	(600-1½)
D			600-2	563	(600-2)	
E			740-2½	703	(800-2½)	

02 DEC 2021 to 30 DEC 2021

02 DEC 2021 to 30 DEC 2021

¹No-NOTAM MP 1200-2000Z++ Sat.

²When ALS inop, increase vis to ½ mile.

³WCH for Group 4 is 16ft.

⁴WCH for Group 4 is 15ft.

⁵When ALS inop, increase vis to 1 mile.

⁶VDA and VGSI not coincident.

⁷When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

⁸WCH for Group 3 is 18ft, Group 4 is 13ft.

⁹WCH for Group 4 is 19ft.

CODED LOST COMMUNICATIONS

SCARLET

TACAN equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand six hundred, proceed direct COSAW, execute TACAN Rwy 23 approach.

GOLD

RNAV/GPS equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand eight hundred, proceed direct HOWEL and execute RNAV/GPS Rwy 23 approach.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

CHERRY POINT MCAS (CUNNINGHAM FLD) (KNKT), Cherry Point, NC

Amdt 3 15JUL21 (21196) (USN)

ELEV 29

RADAR - (E) 118.35x 120.15x 275.6x 299.6x 305.2x 314.8x 320.4x 337.2x 348.0x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	32L ¹ ₃	3.0°/57/1048	ABCDE	126-¼	100	(100-¼)
	14L ³	3.0°/55/1056	ABCDE	126-½	100	(100-½)
	5R ³	3.0°/56/1049	ABCDE	127-½	100	(100-½)
	23R ³	3.0°/57/1076	ABCDE	123-½	100	(100-½)
ASR	23R ⁴		AB	400-½	377	(400-½)
			CDE	400-¾	377	(400-¾)
	32L ²		AB	420-½	394	(400-½)
			CDE	420-¾	394	(400-¾)
	5R		AB	500-1	473	(500-1)
			CDE	500-1¾	473	(500-1¾)
14L		AB	500-1	474	(500-1)	
		CDE	500-1¾	474	(500-1¾)	
C CIR	ALL RWYS		AB	580-1	551	(600-1)
			C	600-1½	571	(600-1½)
			D	600-2	571	(600-2)
			E	700-2½	671	(700-2½)

¹When ALS inop, increase vis CAT ABCDE to ½ mile.

²When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

³CAUTION: PAR RPI and PAPI RRP are not coincident.

⁴When ALS inop, increase vis CAT ABCDE to 1 mile.

02 DEC 2021 to 30 DEC 2021

02 DEC 2021 to 30 DEC 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

NEW RIVER MCAS (MC CUTCHEON FLD)(KNCA), Jacksonville, NC

Amdt 2 22APR21 (21112) (USN)

ELEV 26

RADAR - (U) 118.575 132.2 279.575 289.4 308.4 346.325 350.225 353.875 **▼**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR	1 ¹	3.0°/45/871	ABCD	124-¼	100	(100-¼)
	5 ⁵	3.0°/35/650	ABCD	126-½	100	(100-½)
	19 ⁹	3.0°/41/760	ABCD	123-½	100	(100-½)
	23 ⁴	3.0°/36/656	ABCD	274-¾	250	(300-¾)
PAR W/O GS	1 ²		AB	420-¾	396	(400-¾)
			CD	420-7/8	396	(400-7/8)
	5 ¹⁰		ABCD	400-1	374	(400-1)
	19 ¹¹		ABCD	400-1	377	(400-1)
	23 ⁹		AB	440-1	416	(500-1)
		CD	440-1½	416	(500-1½)	
ASR	5 ^{6 12}		AB	420-1	394	(400-1)
			CD	420-1½	394	(400-1½)
	23 ⁸		ABCD	380-1	356	(400-1)
	19 ⁷		AB	480-1	457	(500-1)
		CD	480-1¾	457	(500-1¾)	
C CIR	ALL RWY		AB	500-1	474	(500-1)
			C	500-1½	474	(500-1½)
			D	580-2	554	(600-2)

¹When ALS inop, increase vis to ½ mile.

²When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1½. The difference between the VGSI TCH (45 ft) and the procedure TCH (49 ft) is greater than 3 ft.

³CAUTION: WCH for aircraft similar to B-1, B-747, C-5, KC-10, is 16 ft.

⁴CAUTION: WCH for aircraft similar to B-727, C-141, P-3 is 16 ft and aircraft similar to B-1, B-747, C-5, KC-10 is 11 ft less than min 20 ft.

⁵CAUTION: WCH for aircraft similar to B-747, C-141, P-3 is 15 ft and aircraft similar to B-1, B-747, C-5, KC-10 is 10 ft less than min 20 ft.

⁶Step down fix 2 NM from thld, 600 min.

⁷Step down fix 2 NM from thld, 700 min.

⁸Step down fix 2 NM from thld, 620 min.

⁹Step down fix 3 NM from RPI, 900 min.

¹⁰Step down fix 2 NM from RPI, 540 min.

¹¹Step down fix 2 NM from RPI, 760 min.

¹²VGSI and descent angle not coincident.

02 DEC 2021 to 30 DEC 2021

02 DEC 2021 to 30 DEC 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

SIMMONS AAF (KFBG), Fort Bragg, NC 1-Amdt 12A 2-Orig A 03DEC20

(20338) (USA)

ELEV 244

RADAR¹ - (E) 120.8 124.2 257.65 284.675 **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
PAR	27	3.0°/36/628	ABC	436-¾	208	(200-¾)
			D	NA	NA	NA
PAR W/O GS	27		AB	640-1	412	(500-1)
			C	640-1¼	412	(500-1¼)
			D	NA	NA	NA
CIR			AB	780-1	536	(600-1)
			C	780-1½	536	(600-1½)
			D	NA	NA	NA
RADAR-2						
PAR	9	3.9°/33/487	COPTER	550-½	309	(400-½)

¹Opr 1200-0400Z++ Mon-Fri, clsd hol. No-NOTAM preventive maint 1800-1900Z++ Fri.

WILMINGTON, NC

Amdt 7A, 17AUG17 (17229) (FAA)

ELEV 32

WILMINGTON INTL (ILM)

RADAR-1 118.25 135.75 284.65 317.425 **T A**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	24		AB	500/24	474	(500-½)	CD	500/50	474	(500-1)
	35		AB	500/40	469	(500-¾)	CD	500/50	469	(500-1)
	17		AB	500-1	468	(500-1)	CD	500-1¾	468	(500-1¾)
	6		AB	540/55	512	(600-1¼)	CD	540-1¾	512	(600-1¾)
C										
CIRCLING	ALL RWY		AB	560-1	528	(600-1)	C	720-2	688	(700-2)
			D	920-3	888	(900-3)				

When control tower closed, ASR NA.

Rwy 17 helicopter visibility reduction below ¾ SM not authorized.

For inop ALS, increase S-24 Cat C/D visibility to 1¾ SM, and S-35 Cats A/B visibility to RVR 5500, and Cat C/D to 1¾ SM.

02 DEC 2021 to 30 DEC 2021

02 DEC 2021 to 30 DEC 2021

RADAR INSTRUMENT APPROACH MINIMUMS