ILS RWY 28C (CAT II & III)

CHICAGO O'HARE INTL (ORD)

LOC/DME I-VZE	APP CRS	Rwy Idg	10800
108.95	273°	TDZE	651
Chan 26 (Y)		Apt Elev	680

From VOGLR: RNAV 1-GPS required.
Aircraft not GPS equipped - RADAR required for procedure entry.
DME or RADAR required.

Simultaneous approach authorized. CAT II: RVR 1000 authorized with specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown.

ALSF-2

MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 on heading 215°and DPA VOR/DME R-082 to DPA VOR/DME and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWERS	GND CON	(TWR CENTER)
135.4	119.0 292.125	128.15 348.0 (Rwy 9L/27R) 133.0 348.0 (10R/28L)	124.125 (TWR NORTH)	121.75 (OBND)
282.225		120.75 121.15 126.9 132.7 348.0 (CENTER)	118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.9 (IBND)

CLNC DEL 121.6 | CPDLC



LOCALIZER 108.95
I-VZE
Chan 26 (Y)

2325

MSA ORD 25 NM
3400

MISSED APCH FIX
DUPAGE
DPA
108.4
Chan 21
R-248 068° 248°

ELEV 680 | D | TDZE 651



HIRL all Rwys
TDZ/CL all Rwys except 4L

1100 | 4000 hdg 215° | DPA R-082 | DPA

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 80).



CATEGORY	A	B	C	D
S-ILS 28C	CAT II RA 105/12 100 DA 751			
S-ILS 28C	CAT III RVR 06			

CATEGORY II & III ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

EC-3, 30 DEC 2021 to 27 JAN 2022
EC-3, 30 DEC 2021 to 27 JAN 2022