WAAS CH 63103 W35A	APP CRS 351°	Rwy ldg 7299 TDZE 2885 Apt Elev 2891

RNAV (GPS) RWY 35
GARDEN CITY RGNL (GCK)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 43°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ⅞ SM, and LNAV Cat C visibility to ⅞ SM. Inop table does not apply to LNAV Cat D.

MALSR

MISSED APPROACH: Climb to 4700 direct WEMDI and hold.

ASOS	KANSAS CITY CENTER	GARDEN CITY TOWER*	GND CON	UNICOM
121.325	125.2 269.4	118.15 (CTAF) L 254.4	119.0 254.4	122.95





CATEGORY	A	B	C	D
LPV DA	3135-½ 250 (300-½)			
LNAV/VNAV DA	3169-½ 284 (300-½)			3169-¾ 284 (300-¾)
LNAV MDA	3200-½ 315 (400-½)			3200-1 315 (400-1)
C CIRCLING	3320-1 429 (500-1)	3360-1 469 (500-1)	3480-1½ 589 (600-1½)	3480-2 589 (600-2)



NC-2, 27 JAN 2022 to 24 FEB 2022
NC-2, 27 JAN 2022 to 24 FEB 2022