

WAAS CH 93733 W06A	APP CRS 063°	Rwy Idg 5950 TDZE 81 Apt Elev 81
--	------------------------	---

RNAV (GPS) RWY 6

OCEAN COUNTY (MJX)

NA Circling Rwy 14, 32 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP -0.3 NA. Inop table does not apply to LPV. For inop MALS, increase LNAV/VNAV all Cats and LNAV Cats A/B visibility to 1. When local altimeter setting not received, use Mc Guire Fld (Joint Base Mc Guire Dix Lakehurst) altimeter setting and increase all DA 41 feet and all MDA 60 feet; increase LNAV Cats C/D visibility 1/8 mile and Circling Cat D visibility 1/4 mile. For inop MALS when using Mc Guire Fld (Joint Base Mc Guire Dix Lakehurst) altimeter setting, increase LPV all Cats visibility to 1/8, LNAV/VNAV all Cats visibility to 1/8, LNAV Cats A/B visibility to 1, and LNAV Cats C/D visibility to 1/8. Helicopter visibility reduction below 3/4 SM NA. VDP and Baro-VNAV NA when using Mc Guire Fld (Joint Base Mc Guire Dix Lakehurst) altimeter setting.

MALS



MISSED APPROACH:
Climb to 600 then climbing right turn to 2000 direct SOITE and hold.

AWOS-3PT
119.875


MC GUIRE APP CON
126.475 363.8

GCO
121.725

UNICOM
122.7 (CTAF) 0



ELEV 81	TDZE 81
121 A	



CATEGORY	A	B	C	D
LPV DA		331-3/4	250 (300-3/4)	
LNAV/VNAV DA		405-3/4	324 (400-3/4)	
LNAV MDA	520-3/4	439 (500-3/4)	520-7/8	439 (500-7/8)
C CIRCLING	520-1 439 (500-1)	560-1 479 (500-1)	580-1 1/2 499 (500-1 1/2)	700-2 619 (700-2)

MIRL Rwy 14-32 **0**
HIRL Rwy 6-24 **0**
REIL Rws 14, 24 and 32 **0**

NE-2, 27 JAN 2022 to 24 FEB 2022

NE-2, 27 JAN 2022 to 24 FEB 2022