

WAAS
CH 86502
W11A

APP CRS
107°

Rwy Idg
4001

TDZE
145

Apt Elev
145

RNAV (GPS) RWY 11

WINTER HAVEN RGNL (GIF)

RNP APCH-GPS

⚠

Rwy 11 helicopter visibility reduction below 1 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Straight-in and Circling Rwy 11 NA at night. When local altimeter setting not received, use Bartow altimeter setting and increase all DA/MDAs 20 feet. Baro-VNAV NA when using Bartow altimeter setting.

MISSED APPROACH:

Climb to 2600 direct RAVYO and hold.

ASOS 133.675	TAMPA APP CON 120.65 290.3	CLNC DEL (GCO) 121.725	UNICOM 123.05 (CTAF) 0
-----------------	-------------------------------	---------------------------	---------------------------

4 NM Holding Pattern

HOVOM

6000
1900

287°

107°

GP 3.00°
TCH 45

JOSIR

1800

OVIKE

2.5 NM to RW11

RW11

*980

6.1 NM

2.5 NM

2.5 NM

2600

RAVYO

*LNAV only.

107° to RW11

4001 X 60

5005 X 100

29

CATEGORY	A	B	C	D
LPV DA	395-1 250 (300-1)			
LNAV/VNAV DA	647-1¾ 502 (600-1¾)			
LNAV MDA	760-1 615 (700-1)	760-1¾ 615 (700-1¾)	760-2 615 (700-2)	760-2 615 (700-2)
CIRCLING	760-1¾ 615 (700-1¾)	820-2 675 (700-2)	960-2 ¾ 815 (900-2 ¾)	960-2 ¾ 815 (900-2 ¾)

REIL Rwy 5 and 23

REIL Rwy 11 and 29 0

MIRL Rwy 5-23 and 11-29 0

WINTER HAVEN, FLORIDA

Orig-B 09SEP21

28°04'N-81°45'W

WINTER HAVEN RGNL (GIF)

RNAV (GPS) RWY 11