

MAYNR ONE DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**

RNAV1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1- GPS.
From SLIPT to CANOA: RNAV 1- GPS.
RADAR required.

ATIS
125.9
CLNC DEL
119.2
GND CON
120.025
OPA LOCKA
134.675 (CT
MIAMI DEP
119.45 290

TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500' per NM to 1000.
 Rwy 9R: Standard with minimum climb of 500' per NM to 700.
 Rwys 12, 27R: Standard with minimum climb of 500' per NM to 600.
 Rwys 27L, 30: Standard with minimum climb of 500' per NM to 520.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K, if unable, advise ATC.

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

SE-3, 19 MAY 2022 to 16 JUN 2022

MAYNR ONE DEPARTURE (RNAV)
(MAYNR1.MAYNR) 19MAY22

MIAMI, FLORIDA
MIAMI-OPA LOCKA EXEC (OPF)