

WAAS

CH **60916**

W29A

APP CRS

286°

Rwy Idg

7504

TDZE

122

Apt Elev

151

RNAV (GPS) RWY 29

GAINESVILLE RGNL (G.N.V.)

▼

▲

DME/DME RNP-0.3 NA. For inoperative MALSR, increase LPV all Cats visibility to RVR 5000 and increase LNAV Cat D visibility to RVR 6000. For inoperative MALSR using Ocala Intl-Jim Taylor Fld altimeter setting, increase LPV all Cats visibility to 1½ mile. When local altimeter setting not received, use Ocala Intl-Jim Taylor Fld altimeter setting and increase LPV DA to 501 feet and all Cats visibility to RVR 5000; increase LNAV/VNAV DA to 561 feet and all Cats visibility to RVR 5000; increase all MDAs 100 feet and increase LNAV Cat C visibility to RVR 4000; increase Circling Cat C visibility ¼ SM and Circling Cat D ½ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). Baro-VNAV and VDP NA when using Ocala Intl-Jim Taylor Fld altimeter setting. When VGSI inoperative, Circling Rwy 25 NA at night.

MALSR

MISSED APPROACH:

Climb to 2100 direct LOLRY and hold.

ATIS	JACKSONVILLE APP CON	GAINESVILLE TOWER★	GND CON	UNICOM
127.15	118.175 338.25	119.55 (CTAF) 0 353.7	121.7	122.95

ELEV 151

TDZE 122

2100

LOLRY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).

TUKSE

4 NM Holding Pattern

JONTU

1 NM to RWY 29

RWY 29

1 NM

3.8 NM

6 NM

GP 3.00° TCH 50

CATEGORY	A	B	C	D
LPV DA		420/24	298 (300-½)	
LNAV/VNAV DA		480/40	358 (400-¾)	
LNAV MDA		500/24	378 (400-½)	500/50 378 (400-1)
CIRCLING	620-1 469 (500-1)	700-1 549 (600-1)	760-1¾ 609 (700-1¾)	820-2 669 (700-2)

GAINESVILLE, FLORIDA

Amdt 1C 20MAY21

29°41'N-82°16'W

GAINESVILLE RGNL (G.N.V.)

RNAV (GPS) RWY 29