



APP CRS	Rwy Idg	7510
312°	TDZE	43
	Apt Elev	46

RNAV (RNP) Z RWY 31
CORPUS CHRISTI INTL (CRP)

▼ For uncompensated Baro-VNAV systems, procedure NA below -1°C (31°F) or above 54°C (130°F). GPS and RF required. For inop MALSR, increase RNP 0.14 all Cats visibility to ¾ mile. * Missed approach requires minimum climb of 335 feet per NM to 500.	MALSR 	MISSED APPROACH: Climb to 2000 on track 312° to ATHIS and hold.
---	-----------	---

ATIS 126.8	CORPUS APP CON 120.9 348.725	CORPUS TOWER 119.4 257.8	GND CON 121.9 269.15	CLNC DEL 118.55
---------------	---------------------------------	-----------------------------	-------------------------	--------------------



2000	ATHIS	See planview for multiple IF locations.	SIWOC
fr 312°			
RW31			
1.7 NM	1.7 NM	5.3 NM	
CATEGORY	A	B	C
RNP 0.14 DA*		303-1/2	260 (300-1/2)
RNP 0.30 DA		384-5/8	341 (400-5/8)

AUTHORIZATION REQUIRED

SC-3, 19 MAY 2022 to 16 JUN 2022

SC-3, 19 MAY 2022 to 16 JUN 2022